

SPECIFICATIONS

Product Description: **VENTILATION BLOWER, HIGH OUTPUT**
Part Number: **9504-50**
Style: **CENTRIFUGAL FAN**

GENERAL DESCRIPTION:

Smart Compact design allows for easy use and storage without sacrificing airflow. Two 8" ports offer positive ventilation or fume extraction. A powerful ¾ HP electric motor is cage-enclosed for protection. Works great with generators. Air delivery certified CEESI.

CONSTRUCTION:

- 8" Flange on intake and exhaust side.
- Tough "safety orange" Polyethylene construction.
- One piece housing with integrated handle
- Black powder coated 16 gauge steel base and motor housing with side mesh for ventilation and cooling.
- Steel fan wheel with aluminum hub.
- Steel zinc plated grill
- Equipped with four (4) rubber feet.

MOTOR:

HP: ¾ HP, UL Listed, CSA Certified.
Voltage: 115 /230 VAC, single Ø, 60 Hz
Max RPM: 3450 (Loaded at 120 Volts, 60 Hz)
Current Draw: 12A (Loaded at 120 Volts, 60 Hz)
Cord: 6.5' 16/3 AWG, SJTW-A Thermoplastic90C 300V Medium Duty
Switch: Toggle ON/OFF with guard.
Plug: NEMA 5-15 Three-prong plug



DUCTING: (Optional)

- Yellow Single-Ply Lightweight Vinyl/polyester, PVC coated,
- 150° F Temp resistant.
- Retractable, Non-collapsible design.
- Hard drawn spring steel wire helix,

DIMENSIONS:

Length	Width	Height	Weight
16"	18.5"	20"	45 Lbs

FLOW RATES: (flow rates meas. with 15' of 8" ducting)

Free Air	One 90° Bend	Two 90° Bends
1570 CFM	1100 CFM	900 CFM