



**FIELD ENVIRONMENTAL
INSTRUMENTS, INC.**

Experience beyond rentals.

- Rentals
- Supplies
- Sales
- Service

BESST PANACEA P125



**CARRIED
EXCLUSIVELY
BY FEI**

- ZIST wells as narrow as 1.25" diameter
- Constructed of 316 stainless steel for high pressure applications, maximum durability
- Built with a standard 80 micron Poly filter at the intake to prevent sediment from interfering with valves
- Filter connection can be easily modified with a drop tube to customize the intake depth

Body Material	316 Stainless Steel
Length (in.)	12.5
Outer Diameter (in.)	1.13
Weight (lbs.)	1.4
Maximum Depth (ft. bgs.)	3000
Minimum Submergence (ft.)	6 ft. with Volume Booster
Internal Volume (mL)	0
Standard Filter Pore Size (µm)	80, others available
Standard Tubing OD (in.)	1/4, others available
Seal Material	Buna-N, others available
Gas Compatibility	Nitrogen, compressed air
ZIST Compatibility	1.25" SCH40, 1.25" SCH80



Pittsburgh, PA
800-393-4009

Atlanta, GA
866-620-6762

Chicago, IL
844-515-9170

Houston, TX
866-323-4006

Kansas City, KS
866-580-5499

fieldenvironmental.com
info@fieldenvironmental.com

Long Beach, CA
844-608-3344

Los Angeles, CA
866-278-2382

Minneapolis, MN
866-580-5512

Philadelphia, PA
866-648-8607

Portland, OR
855-398-5600

Seattle, WA
855-398-5600