

GasAlert MaxXT II

multi-gas detector



Go the distance, and save

GasAlertMax XT II is the smart, simple, economical way to compliance. Workers feel safe and incidents are minimized so everyone will be able to do more. That means savings realized from business continuity and productivity.

Simple operation, with SmartSample pump.

GasAlertMax XT II reliably monitors up to four hazards and combines straightforward one-button operation with our robust, motorized pump for intelligent, remote sampling, ideal for confined spaces. The GasAlertMax XT II is fully compatible with MicroDock II automated test and calibration system.



**WATER
RESISTANT**



- Minimize costs and training with one-button operation
- More accurate sampling results with SmartSample pump technology
- Compact, comfortable and field tough

BW
Technologies
by Honeywell

Wear yellow. Work safe.

H₂S

CO

O₂

LEL

Standard features of BW products:

- Continuous LCD shows real-time gas concentrations
- Compact and lightweight design makes it comfortable to wear
- Water-resistant
- Simple automatic calibration procedure; compatible with BW MicroDock II automatic test and calibration station
- Full function self-test of sensor, battery status, circuit integrity and audible/visual alarms on start up
- Bright wide-angled visual alarm bars
- Built-in concussion-proof boot

GasAlertMax XT II Specifications

Size	5.1 x 2.8 x 2.0 in. / 13.1 x 7.0 x 5.2 cm																			
Weight	11.5 oz. / 328 g																			
Temperature	-4 to 122°F / -20 to 50°C																			
Humidity	10 - 100% RH (non-condensing)																			
Alarms	- Visual, vibrating, audible (95dB) - Low, High, STEL, TWA, OL (over limit), Low Battery, Pump																			
Tests	Audible/visual alarms on activation, sensors, battery, pump and circuitry (continuous)																			
Typical battery life	13 hours @ 32°F / 0°C 8 hours @ -4°F / -20°C Recharges in 6 hours																			
Pump draw	Sample from up to 75 ft. / 23 m																			
User options	<table><tr><td>Confidence beep</td><td>Force calibration when overdue</td></tr><tr><td>Safety (sensor) lock</td><td></td></tr><tr><td>Latching alarms</td><td>Sensor configuration</td></tr><tr><td>Safe display mode</td><td>Detector identification</td></tr><tr><td>Calibration IR lock</td><td>Low alarm acknowledge</td></tr><tr><td>Location selection</td><td>Language choices (five)</td></tr><tr><td>Force block test</td><td>Set custom start-up message</td></tr><tr><td>Force bump test when overdue</td><td>Confidence interval</td></tr><tr><td></td><td>Datalog interval</td></tr></table>		Confidence beep	Force calibration when overdue	Safety (sensor) lock		Latching alarms	Sensor configuration	Safe display mode	Detector identification	Calibration IR lock	Low alarm acknowledge	Location selection	Language choices (five)	Force block test	Set custom start-up message	Force bump test when overdue	Confidence interval		Datalog interval
Confidence beep	Force calibration when overdue																			
Safety (sensor) lock																				
Latching alarms	Sensor configuration																			
Safe display mode	Detector identification																			
Calibration IR lock	Low alarm acknowledge																			
Location selection	Language choices (five)																			
Force block test	Set custom start-up message																			
Force bump test when overdue	Confidence interval																			
	Datalog interval																			
Ratings	EMI/RFI: Complies with EMC Directive 2004/108/EC																			
Ingress Protection	IP66/67																			
Certifications and approvals	<table><tr><td></td><td>Class I, Div. 1, Gr. A, B, C, D</td></tr><tr><td>IECEX:</td><td>Ga Ex ia IIC T4</td></tr><tr><td>ATEX:</td><td>CE  II 1 G Ga Ex ia IIC T4</td></tr><tr><td></td><td>Br Ex ia IIC T4</td></tr></table>			Class I, Div. 1, Gr. A, B, C, D	IECEX:	Ga Ex ia IIC T4	ATEX:	CE  II 1 G Ga Ex ia IIC T4		Br Ex ia IIC T4										
	Class I, Div. 1, Gr. A, B, C, D																			
IECEX:	Ga Ex ia IIC T4																			
ATEX:	CE  II 1 G Ga Ex ia IIC T4																			
	Br Ex ia IIC T4																			
Warranty	Full two year warranty including all sensors																			

Additional GasAlertMax XT II features:

- Integrated sampling pump with reliable diaphragm technology
- Best in class block detection with semi-conductor pressure sensor
- Multi-language support in English, French, German, Spanish and Portuguese
- Conveniently manage your detector with Fleet Manager II
- Equipped with standard datalogging and event logging

Options and Accessories



MicroDock II compatible



Belt holster



Multi-unit cradle charger



Concussion-proof boot


For a complete list of accessories, please contact BW Technologies by Honeywell.

Sensor Specifications

Gas	Measuring Range	Resolution
H ₂ S	0-200 ppm	1 ppm
CO	0-1000 ppm	1 ppm
O ₂	0-30.0%	0.1%
Combustible gases	0-100% LEL 0-5.0% v/v	1% 0.1%

Alarm setpoints for all sensors are user adjustable. Setpoint(s) are automatically displayed during instrument start-up.

Locally available from



Corporate Headquarters

2840 - 2 Avenue S.E.
Calgary, AB, Canada T2A 7X9
Phone: +1.403.248.9226
Toll free: 1.800.663.4164

www.gasmonitors.com

USA 1.888.749.8878
Europe +44 (0)1295.700.300
France +33 (0) 442.98.17.70
Germany 49 (0) 2137.17.6522

info@gasmonitors.com

Middle East +971.4.887.1766
S.E. Asia +65.6580.3468
China +86.10.6786.7305
Australia +61.3.9464.2770

Latin America +55.11.3475.1873
Other Countries +1.403.248.9226

6570-0-EN
© 2010 Honeywell International Ltd. All Rights Reserved.

DUE TO ONGOING RESEARCH AND PRODUCT IMPROVEMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.