



GasAlert MicroClipXT

multi-gas detector



Multi-gas made easy

The slim and compact GasAlertMicroClip XT provides affordable protection from atmospheric hazards. With continuous visual confirmation of detector operation and compliance provided by the IntelliFlash™ feature. Simple one-button operation for the ultimate ease of use significantly reduces training times. The GasAlertMicroClip XT is fully compatible with BW's MicroDock II automatic test and calibration system and Fleet Manager 2 desktop software.



H₂S

CO

O₂

LEL

- Incredibly thin and lightweight, making it comfortable to wear
- Multi-gas versatility with one-button simplicity
- Continuous visual compliance with IntelliFlash
- Extraordinarily low cost of ownership

**WATER
RESISTANT** 



BW
Technologies
by Honeywell

Wear yellow. Work safe.

Standard features of BW products:

- Continuous LCD shows real-time gas concentrations
- Compact and lightweight design makes it comfortable to wear
- Water-resistant
- Simple automatic calibration procedure; compatible with BW MicroDock II automatic test and calibration station
- Full function self-test of sensor, battery status, circuit integrity and audible/visual alarms on start up
- Bright wide-angled visual alarm bars
- Built-in concussion-proof boot

GasAlertMicroClip Specifications

Size	4.4 x 2.4 x 1.1 in. / 11.3 x 6.0 x 2.9 cm																							
Weight	6 oz. / 171 g																							
Temperature	-4 to +122°F / -20 to +50°C																							
Humidity	0% - 95% RH (non-condensing)																							
Alarms	- Visual, vibrating, audible (95 dB) - Low, High, STEL, TWA, OL (over limit)																							
Tests	Audible/visual alarms on activation, sensors, battery and circuitry (continuous)																							
Pump	Compatible with the Sampler motorized sampling pump																							
Typical battery life*	10 hours (typical); recharges in less than 4 hours																							
User options	<table><tr><td>Confidence beep</td><td>Combustible gas measurement (% LEL or % by volume methane)</td></tr><tr><td>Set STEL interval</td><td></td></tr><tr><td>Sensor on/off</td><td>User-settable calibration gas level</td></tr><tr><td>Latching alarms</td><td></td></tr><tr><td>Safe display mode</td><td>Force bump test when overdue</td></tr><tr><td>Stealth mode</td><td></td></tr><tr><td>Calibration lock</td><td>Force calibration when overdue</td></tr><tr><td>Auto zero on start up</td><td>Low alarm acknowledge</td></tr><tr><td>O₂ auto calibration on start up</td><td>Language choices (five)</td></tr><tr><td>Set bump test interval</td><td>Set custom start up message</td></tr><tr><td>IntelliFlash interval</td><td></td></tr></table>		Confidence beep	Combustible gas measurement (% LEL or % by volume methane)	Set STEL interval		Sensor on/off	User-settable calibration gas level	Latching alarms		Safe display mode	Force bump test when overdue	Stealth mode		Calibration lock	Force calibration when overdue	Auto zero on start up	Low alarm acknowledge	O ₂ auto calibration on start up	Language choices (five)	Set bump test interval	Set custom start up message	IntelliFlash interval	
Confidence beep	Combustible gas measurement (% LEL or % by volume methane)																							
Set STEL interval																								
Sensor on/off	User-settable calibration gas level																							
Latching alarms																								
Safe display mode	Force bump test when overdue																							
Stealth mode																								
Calibration lock	Force calibration when overdue																							
Auto zero on start up	Low alarm acknowledge																							
O ₂ auto calibration on start up	Language choices (five)																							
Set bump test interval	Set custom start up message																							
IntelliFlash interval																								
Ratings	EMI/RFI: Complies with EMC Directive 2004/108/EC																							
Certifications and approvals	 Class I, Div. 1, Gr. A, B, C, D ATEX:  II 1 G Ex ia IIC T4 Ga IECEX: Ex ia IIC T4 Ga CE: European Conformity																							
Warranty	Full two-year warranty including all sensors																							

*Runtime on a new instrument at 20°C / 68°F. Approximately 20% capacity loss is normal with lithium polymer batteries after 500 charge cycles. Refer to the Operator's Manual for additional information.



Corporate Headquarters

2840 - 2 Avenue S.E.
 Calgary, AB, Canada T2A 7X9
 Phone: +1.403.248.9226
 Toll free: 1.800.663.4164

www.gasmonitors.com

USA 1.888.749.8878
 Europe +44 (0)1295.700.300
 France +33 (0) 442.98.17.70
 Germany 49 (0) 2137.17.6522

info@gasmonitors.com

Middle East +971.4.450.5852
 S.E. Asia +65.6580.3468
 China +86.10.6786.7305
 Australia +61.3.9464.2770

Latin America +55.11.3309.1030
 Other Countries +1.403.248.9226

Additional GasAlertMicroClip XT features:

- IntelliFlash verifies operation and compliance to both the user and supervisor
- Tamper-proof, one button operation
- Compatible with the Sampler motorized remote sampling pump
- Equipped with internal vibrating alarm for high noise areas
- Powered by a lithium polymer battery
- Multi-language support in English, French, German, Spanish and Portuguese
- Conveniently manage your fleet using Fleet Manager II

Options and Accessories



MicroDock II compatible



Auxiliary filter kit



IR connectivity kit




Five unit cradle charger

For a complete list of accessories, please contact BW Technologies by Honeywell.

Sensor Specifications

Gas	Measuring Range	Resolution
H₂S	0-100 ppm	1 ppm
CO	0-500 ppm	1 ppm
O₂	0-30.0%	0.1%
Combustible gases	0-100% LEL 0-5.0% v/v	1% 0.1%
Alarm setpoints for all sensors are user adjustable. Setpoints are automatically displayed during instrument start up.		

Locally available from



DUE TO ONGOING RESEARCH AND PRODUCT IMPROVEMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.