

E•A•R® CLASSIC® EARPLUGS

E•A•R Classic



World's Most Popular Earplug.

E•A•R Classic Earplugs were the first foam earplugs ever. Today, they are still the leading seller across the world because of their outstanding advantages including: Excellent Protection - NRR 29dB; Easy To Use Cylinder Shape; Soft, Low Pressure Foam for All-Day Comfort; Non-Allergenic; Moisture Resistant and Non-Flammable; Yellow for High Visibility.

E•A•R Classic earplugs are the proven performers.

Proven Size. E•A•R Classic has tested to be the right size to fit the widest range of ear canals (Mil P37407).

Proven Shape. Its cylindrical-shape has shown to protect better than tapered plugs (British Steel Technical, 1994).

Proven Foam. E•A•R is the only manufacturer to make its own PVC foam, so it can regularly test for optimum and consistent performance. (Human Factors, 1990).

No wonder they've been the most requested hearing protector in the world for over 30 years.

E•A•R Classic Earplugs. Put them to your test.



E•A•R Classic

Is Offered In Several Packages And Dispenser Box Quantities To Meet User Needs.

How To Order

| PRODUCT CODE | PRODUCT | UPC | QTY/BOX | BOXES/CASE | PR/CASE | CASE WEIGHT | CASE LENGTH | CASE WIDTH | CASE HEIGHT |
|--------------|------------------------------------|--------------|---------|------------|---------|-------------|-------------|------------|-------------|
| 312-1201 | Classic Plug/Pillow Pack | 080529100009 | 200 | 10 | 2000 | 17.00 | 19.25 | 12.50 | 31.50 |
| 312-1201 | Classic Plug in Poly Bag | 080529120021 | 200 | 10 | 2000 | 8.30 | 19.75 | 16.00 | 24.50 |
| 311-1101 | Classic Plug w/Cord | 080529110015 | 200 | 10 | 2000 | 22.40 | 19.25 | 12.50 | 31.50 |
| 390-1000 | Classic Value Pack Dispenser | 080529900005 | 200 | 10 | 2000 | 5.67 | 27.25 | 11.50 | 7.25 |
| 316-1111 | Classic Plug 5 Pr. Pkg. | 080529160003 | 250 | 16 | 4000 | 19.20 | 23.00 | 19.50 | 14.75 |
| 311-1110 | Classic Plug w/Cord Paper Bag | 080529110060 | 75 | 10 | 750 | 13.40 | 19.25 | 12.50 | 31.50 |
| 311-4101 | Classic Plug-Metal Det. w/Cord | 080529110312 | 200 | 10 | 2000 | 23.20 | 19.25 | 12.50 | 31.50 |
| 311-1081 | Classic Econopack Corded | 080529110817 | 500 | 3 | 1500 | 14.20 | 28.75 | 12.75 | 15.25 |
| 312-1080 | Classic Econopack UnCorded | 080529110800 | 500 | 10 | 5000 | 21.00 | 19.75 | 16.00 | 24.50 |
| 312-1082 | Classic Econopack UnCorded | 080529110824 | 1000 | 3 | 3000 | 12.50 | 28.75 | 12.75 | 15.25 |
| 391-1001 | Classic One Touch Refill | 080529910011 | 500 | 4 Bottles | 2000 | 6.10 | 8.50 | 7.50 | 9.00 |
| 310-1060 | Classic 30-Pair Pack | 080529100702 | 30 | 12 | 360 | 5.625 | 19.50 | 10.00 | 7.00 |
| 310-1101 | Classic Plus/Pillow Pack | 080529100511 | 200 | 10 | 2000 | 20.00 | 19.25 | 12.50 | 31.50 |
| 311-1105 | Classic Plus in Poly Bag | 080529110237 | 200 | 10 | 2000 | 24.00 | 19.25 | 12.50 | 31.50 |
| 310-1103 | Classic Small/Pillow Pack | 080529100528 | 200 | 10 | 2000 | 16.50 | 19.25 | 12.50 | 31.50 |
| 311-1106 | Classic Small in Poly Bag | 080529110244 | 200 | 10 | 2000 | 22.10 | 19.25 | 12.50 | 31.50 |
| 391-1007 | Classic Platinum™ One Touch Refill | 080529910073 | 500 | 4 Bottles | 2000 | 6.10 | 8.50 | 7.50 | 9.00 |
| 310-4002 | Classic Platinum Plug/Pillow Pack | 080529100481 | 200 | 10 | 2000 | 17.0 | 19.25 | 12.50 | 31.50 |
| 310-4003 | Classic Platinum Plug in Polybag | 080529100573 | 200 | 10 | 2000 | 7.84 | 19.75 | 16.00 | 24.50 |

ANSI S3.19-1974 E-A-R Classic

| Test Frequency (Hz) | 125 | 250 | 500 | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 | NRR | CSA CLASS |
|-------------------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-----------|-----------|
| Mean Attenuation (dB) | 37.4 | 40.9 | 44.8 | 43.8 | 36.3 | 41.9 | 42.6 | 46.1 | 47.3 | 29 | AL |
| Standard Deviation (dB) | 5.7 | 5.0 | 3.3 | 3.6 | 4.9 | 3.0 | 3.1 | 3.5 | 2.7 | | |

ANSI S3.19-1974 E-A-R Classic Platinum

| Test Frequency (Hz) | 125 | 250 | 500 | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 | NRR | CSA CLASS |
|-------------------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-----------|-----------|
| Mean Attenuation (dB) | 32.9 | 37.5 | 41.4 | 40.0 | 36.4 | 43.9 | 45.2 | 48.2 | 48.1 | 30 | AL |
| Standard Deviation (dB) | 4.2 | 4.4 | 4.2 | 4.3 | 4.0 | 3.0 | 2.5 | 2.6 | 4.4 | | |

AS/NZS 1270:200 E-A-R Classic sin cordón

| Test Frequency (Hz) | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 | SLC ₈₀ | CLASS |
|-------------------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------------|----------|
| Mean Attenuation (dB) | 19.8 | 20.6 | 27.8 | 27.4 | 31.0 | 38.7 | 41.2 | 22.5 | 4 |
| Standard Deviation (dB) | 9.2 | 8.6 | 7.3 | 8.7 | 6.3 | 6.1 | 9.2 | | |
| Mean minus SD | 10.6 | 12.0 | 20.5 | 18.7 | 24.7 | 32.6 | 32.0 | | |

AS/NZS 1270:2002 E-A-R Classic Corded

| Test Frequency (Hz) | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 | SLC ₈₀ | CLASS |
|-------------------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------------|----------|
| Mean Attenuation (dB) | 19.0 | 19.0 | 25.1 | 23.9 | 30.7 | 37.0 | 39.3 | 21 | 3 |
| Standard Deviation (dB) | 6.7 | 5.1 | 7.9 | 7.5 | 6.9 | 5.5 | 9.0 | | |
| Mean minus SD | 12.3 | 13.9 | 17.2 | 16.4 | 23.8 | 31.5 | 30.3 | | |

AS/NZS 1270:2002 E-A-R Classic Platinum

| Test Frequency (Hz) | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 | SLC ₈₀ | CLASS |
|-------------------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------------|----------|
| Mean Attenuation (dB) | 19.8 | 20.5 | 27.0 | 28.5 | 30.4 | 38.1 | 40.9 | 23 | 4 |
| Standard Deviation (dB) | 6.3 | 6.6 | 8.8 | 7.9 | 6.6 | 5.5 | 5.6 | | |
| Mean minus SD | 13.5 | 13.9 | 18.2 | 20.6 | 23.8 | 32.6 | 35.3 | | |