

Differential Pressure Manometer

Measures Gauge/Differential Pressure from 0 to 138.5 inH₂O (inches of water)

Features:

- 11 selectable units with Max/Min recording and Relative time stamp
- Compensated temperature range 32 to 122°F (0-50°C)
- Data Hold, Auto power off, and Min/Max functions
- Large LCD display with backlighting
- Zero function for offset correction or measurement
- Built-in RS-232 interface (optional software and cable)
- Includes 9V battery, connection hose and ABS carrying case

Applications

- HVAC
- Fume Hoods
- Pneumatic controls
- Hydraulics
- Medical equipment
- Clean rooms

€

Specifications:	Range	Resolution	Basic Accuracy
inH ₂ 0:	±138.3inH ₂ 0	0.1inH ₂ 0	±3%FS
psi:	±5.000psi	0.001psi	±3%FS
bar:	±0.344bar	0.001bar	±3%FS
mbar:	±344.7mbar	0.1mbar	±3%FS
kPa:	±34.47kPa	0.01kPa	±3%FS
inHg:	±10.18inHg	0.01inHg	±3%FS
mmHg:	±258.5mmHg	0.1mmHg	±3%FS
ozin ²	±80.00ozin ²	0.01ozin ²	±3%FS
ftH ₂ 0:	±11.53ftH ₂ 0	0.01ftH ₂ 0	±3%FS
cmH ₂ 0:	±350.1cmH ₂ 0	0.1cmH ₂ 0	±3%FS
kgcm ^{2:}	±0.351kgcm ²	0.001kgcm ²	±3%FS
Dimensions:	7.1x2.8x1.1" (182x72x30mm)		
Weight:	5.3oz (150g)		

Ordering Information

406800Digital Manometer with PC Interface 406800-NIST ...Digital Manometer with NIST Certificate 407752PC Software and Cable

EXTECH INSTRUMENTS CORPORATION 285 Bear Hill Road, Waltham, MA 02451-1064, U.S.A.

Phone: 781-890-7440 • FAX 781-890-7864







ISO 9001:2000 CERTIFIED

Copyright @ 2004 Extech Instruments Corporation. All rights reserved including the right of reproduction in whole or in part in any form.