

- Rentals
- Supplies
- Sales
- Service

ENVIRONMENTAL EQUIPMENT AND FIELD SUPPLIES



Portable Pumping and Sampling System



FEATURES


- Lightweight aluminum
- One-person portability
- 250' HAPPY HOSE!* capacity
- Easy decontamination
- Cable guide for HAPPY HOSE!*
- Installs vertically or horizontally
- Locking holster for pump storage
- Removable reel handle
- Can be shipped UPS

DESCRIPTION

The REEL E-Z is a compact system designed to provide a convenient way to store and operate the Grundfos® RediFlo-2* Pump. When used with INW's HAPPY HOSE! (cable, tubing and safety cable bonded together) the system easily installs the pump in the well, locks it in place and allows for easy take up and cleaning without cable entanglement. The roller guide protects the cable from well damage and the REEL E-Z can accommodate both above and below-grade well applications.

OPERATION

The REEL E-Z system is used in portable sampling and pumping applications in small diameter wells as deep as 250 feet. The system can be purchased with optionally installed check valve to prevent back flow, or with a wheel kit for easier transport. INW also now offers the system installed only with Happy Cable! (combination electrical conductors and safety wire rope) for customers that want to use the system with various types of tubing.



APPLICATIONS


■ High & low flow sampling




- Rentals
- Supplies
- Sales
- Service



DIMENSIONS AND SPECIFICATIONS





DISCHARGE FITTING FLECTEIGAL JUNCTION BOX

BEDI-FLO2 PUMP

HOLSTER

HOW TO ORDER

- · Specify REEL E-Z system.
- · Specify HAPPY HOSE! or HAPPY CABLE! material.
- · Order options and accessories as needed.

REEL E	Z SYSTEMS w/ HAPPY HOSE!/CABLE!
3P015	100' REEL E-Z System w/ PVC HAPPY HOSE!
3P030	200' REEL E-Z System w/ PVC HAPPY HOSE!
3P302	150' REEL E-Z System w/ TLPE HAPPY HOSE!
3P304	250' REEL E-Z System w/ TLPE HAPPY HOSE!
3P333	250' REEL E-Z System w/ PE HAPPY CABLE!
ACCESS	ORIES
3P853	Variable Frequency Drive (VFD)
3P210	1/2" ID Tubing Check Valve-Option (factory installed)
3P212	3/8" ID Tubing Check Valve-Option (factory installed)
3J115	.45µm High-Capacity, In-Line Filter
3P175	Removable Pump Shroud
	Wheel Kit

MECHANICAL

Weight (without pump & hose)	25 lbs.
Materials of	Aluminum, PE,
Construction	300 Series S.S.
HAPPY HOSEI	PVC: 200"
Capacity	TLPE: 250'
HAPPY CABLE!	250'
Capacity	
Discharge Fitting	3/4" S.S. standard
	garden hose thread
Cable Guide	8" diameter
Sample Hose	PVC 16'
Length	TLPE 8"

ELECTRICAL		
Electrical Connector	NEMA 6P rating 4 pole quick connect	
Junction Box HAPPY CABLE!	NEMA 6P rating	
O.D. Jacket Motor Lead	7/16" PVC, PE or FEP Teflon PVC, Teflon or PE Insulated 18 AWG wire	
Converter Cable Length	12"	