



HERON
INSTRUMENTS
Groundwater Monitoring INC.

dipper-T Water Level Meter

Now with **drawDown** Mode

Length options: 50ft/15m to 2000ft/600m

Warranty: 5 years, probe 1 year

The **dipper-T** water level meter is a topline, top quality instrument used for measuring **static** and **falling** head levels in wells and boreholes. With a touch of a button the unit changes from **static** to **drawDown** mode; a dual function unit at an affordable price.

The **dipper-T** in **static** mode is used for measuring the depth of water in wells, boreholes and standpipes. The **dipper-T** in **drawDown** mode may be used for measuring **falling** water levels during purging, well development and for low flow sampling; helping to protect your pumps from damage caused by dry running.



Features included with the dipper-T:

- **Electronic Module (IP65)** – mode selectable for **static** and **drawDown** levels, removable for easy cleaning and servicing
- **Probe (IP68)** – fully pressure/depth rated, **field replaceable** for optional casing or bottom detector probes
- **Steel Tape** – high tensile steel, jacketed with polyethylene, high break strength, stretch resistant and lifelong legibility
- **Padded Carry Case** – to protect your **precision** water level meter from the elements
- **Tape Guide And Hanger** – to support the meter at the well head and to **protect** the tape from sharp edges on the well casing
- **Vinyl Holding Grip** – molded to the frame, **ergonomic** easy grip
- **Winding Handle** – custom made for **easy** **rewinding** with gloved hands

Available options:







- Narrow 3/8 inch probe (not removable)
- Well depth indicator probe
- Well casing indicator probe
- Potable Water only model

www.heroninstruments.com



WATER LEVEL METERS

SELECTION GUIDE:


| | | Tape (see below for details) | drawDown Electronics | Fully Submersible Probe | Field Replaceable Probe | 3/8" Narrow Probe Available (not detachable) | Tape Guide and Hanger | Audio/Visual Sensor | 9 Volt Battery | Temperature | Padded Carry Case | Cloth Carry Case | 5 Year Product and 1 Year Probe Warranty * | 3 Year Product and 1 Year Probe Warranty * | Tape Lengths ** |
|---|---|------------------------------|----------------------|-------------------------|-------------------------|--|-----------------------|---------------------|----------------|-------------|-------------------|------------------|--|--|--------------------------|
| WATER LEVEL METERS |  dipper-T | A | • | • | • | • | • | • | • | | • | | • | | 50ft/15m to 1000ft/300m |
| |  Water Tape | C | | • | | • | • | • | • | | | • | | • | 100ft/30m to 1000ft/300m |
| |  Little Dipper | A | • | • | • | • | • | • | • | | • | | | • | 75ft / 22m |
| |  mega reel | A C | • | • | • | • | | • | • | | • | | | • | 1500ft/400m and up |
| CONDUCTIVITY/ TEMPERATURE WATER LEVEL METERS |  Conductivity Plus | A | | • | • | | • | • | • | • | • | | | • | 100ft/30m to 1000ft/300m |
| |  Temperature Meter | B | | • | • | | • | • | • | • | • | | | • | 100ft/30m to 500ft/150m |

* Warranties cover manufactured defect.


** Longer tape lengths and Power Reel are available.



Fully pressure/
depth rated, IP68
field replaceable probes




Tape Guide and Hanger



A = High tensile steel tape, jacketed with polyethylene, high break strength, stretch resistant and lifelong legibility



Padded Carry Case



Rewinding Handle and
Vinyl Holding Grip

B = High tensile steel tape, jacketed with heat and hydrocarbon resistant Kynar, high break strength, stretch resistant and lifelong legibility



C = White polyethylene tape, reinforced with stretch resistant Kevlar

HERON INSTRUMENTS INC.

447 Moxley Rd. SS 106 | Dundas, ON Canada L9H 5E2 | TF: 800-331-2032 | T: 905-628-4999 | info@heroninstruments.com

Please visit our website www.heroninstruments.com for more information on the complete Heron line.

🇨🇦 Made in Canada