

Type II Cans have two openings!

Compliant Type II steel safety cans offer additional convenience with two openings at the top. One opening is equipped with a flexible metal hose for smooth, accurate pouring into small apertures. The hose also provides a bonding path to a receiving vessel. A second opening, positioned behind the handle, is used for filling. All Type II Cans have a swinging handle to ease carrying a full, heavy can. During pouring, Justrite's unique design uses the weight of the liquid to counterbalance the pressure required to open the spout. Both openings are equipped with dual-density flame arresters which reliably dissipate heat to prevent flashback ignition. Both openings self-close to prevent spillage and the rear opening automatically vents between 3 and 5 psig to guard against pressure build-up at elevated temperatures and potential explosion.



Heavy-duty, coated steel with reinforcing ribs and tough powder paint finish offers exceptional on-the-job durability. Justrite's quality is backed by an exclusive Ten-Year Warranty. All cans meet OSHA and NFPA, are FM Approved and UL/ULC Listed.

Type II Red Safety Cans for Flammables

Description and Capacity	Hose Dimensions Outer Dia. x L	Can Dimensions Outer Dia. x H	Approv./Lstg. Regulation	Ship Wt. Ctn. (Lbs/Kg)	Model No.
1 gallon steel safety can with hose	.625" x 9"	9.375" x 6.5"	FM,UL	7/3	10327
2 gallon steel safety can with hose	.625" x 9"	9.5" x 12.625"	FM,UL	8/4	10527
3 gallon steel safety can with hose	1" x 9"	11.5" x 13.5"	FM,UL,ULC	8/4	10721
3 gallon steel safety can with hose	.625" x 9"	11.5" x 13.5"	FM,UL,ULC	8/4	10728
5 gallon steel safety can with hose	1" x 9"	11.5" x 17"	FM,UL,ULC	9/4	10821
5 gallon steel safety can with hose	.625" x 9"	11.5" x 17"	FM,UL,ULC	9/4	10828