



Koby Environmental

Manufacturers of Environmental Groundwater Testing Equipment



Torquer Locking Well Plugs

- No metal parts.
- Simple to use reliable locking system.
- Accepts #1 or #3 type pad locks or Koby Safety Lock-Out Tags.
- High-tech liquid tight seamless dual rubber gasket.
- Easily disassembled in the field for decon.
- Strong instrument tethering tool. Dual use with anvil tip.
- Manufactured from an engineering grade polymer blend commonly used to replace steel gears in industry, resistant to most chemicals, unaffected by freezing or high temperatures.



- Smooth acting ergo grip. Easy on, easy off wing nut.
- Large, bold, easy to read well ID lettering.
- Bright safety coloring.
- Light weight, yet super strong.
- Flush OD design for easy well installation.

- Advanced engineered design will not separate in well.

- Easily convertible for vapor extraction, pressure gauges, vacuum gages and threaded line fittings.

- Domed top prevents liquids from pooling.
- Designed, engineered and manufactured in the U.S.A.

- Available worldwide through authorized distributors.



"Specified by groundwater professionals"

U.S. patent awarded



Koby Environmental

Manufacturers of Environmental Groundwater Testing Equipment

Torquer Locking Well Plugs



Manufactured by Koby from 100% Dupont® Nylon



1/2"	3/4"	1"	1 1/4"	1 1/2"
2"	2 1/2"	3"	4"	
5"				6"

Current Sizes Available:

- 1/2"
- 3/4"
- 3/4" 80
- 1"
- 1 1/4"
- 1 1/2"
- 2"
- 2" 80
- 2 1/2"
- 3"
- 3 1/2"
- 4"
- 4 1/2"
- 4" 80
- 5"
- 5 1/2"
- 6"
- 6 1/2"
- 8"



Koby Environmental

Manufacturers of Environmental Groundwater Testing Equipment

Torquer Locking Well Plugs



Manufactured by Koby from 100% Dupont® Nylon



Box Size Specification Guide

PIPE	PART #	DESCRIPTION	FITS	Weight	BOX Qty.
1/2"	T.5	1/2" Torquer	Sched. 40/80	1.7 oz.	25/50
3/4"	T.75	3/4" Torquer	Sched. 40	1.9 oz.	25/50
3/4" 80	T.75-80	3/4" Torquer	Sched. 80	1.8 oz.	25/50
1"	T1	1" Torquer	Sched. 40/80	1.7 oz.	50/100/200/400
1 1/4"	T1.25	1 1/4" Torquer	Sched. 40/80	1.9 oz.	50/100/200
1 1/2"	T1.5	1 1/2" Torquer	Sched. 40/80	2.1 oz.	50/100/200
2"	T2	2" Torquer	Sched. 40	3.4 oz.	50/100/200
2" 80	T2 80	2" Torquer	Sched. 80	3.3 oz.	50/100/200
2 1/2"	T2.5	2 1/2" Torquer	Sched. 40/80	4.6 oz.	50/100
3"	T3	3 1/2" Torquer	Sched. 40/80	6.4 oz.	25/100
3 1/2"	T3.5	3 1/2" Torquer	Custom	7.0 oz.	Select
4"	T4	4" Torquer	Sched. 40	9.9 oz.	25/50
4 1/2"	T4.5	4 1/2" Torquer	Custom	10.4 oz.	Select
4" 80	T4 80	4" Torquer	Sched. 80	9.2 oz.	25/100
5"	T5	5" Torquer	Sched. 40/80	10.6 oz.	25
5 1/2"	T5.5	5 1/2" Torquer	Custom	17.5 oz.	Select
6"	T6	6" Torquer	Sched. 40/80	27.0 oz.	12
6 1/2"	T6.5	6 1/2" Torquer	Custom	27.0 oz.	Select
8"	T8	8" Torquer	Sched. 40/80	TBA	





Koby Environmental

Manufacturers of Environmental Groundwater Testing Equipment

Torquer Locking Well Plugs



Manufactured by Koby from 100% Dupont® Nylon



Size Specification Guide

PIPE	PART #	DESCRIPTION	MIN. SIZE	MAX. SIZE
1/2"*	T.5	1/2" Torquer	.500" (12.5mm)	.725" (18.5mm)
3/4"	T.75	3/4" Torquer	.750" (19mm)	1.100" (28mm)
3/4" 80	T.75-80	3/4" Torquer	.680" (17mm)	.950" (24mm)
1"*	T1	1" Torquer	.925" (23.5mm)	1.260" (32mm)
1 1/4"*	T1.25	1 1/4" Torquer	1.220" (31mm)	1.620" (41mm)
1 1/2"*	T1.5	1 1/2" Torquer	1.450" (37mm)	1.870" (48mm)
2"	T2	2" Torquer	1.990" (50mm)	2.460" (62.5mm)
2" 80	T2 80	2" Torquer	1.865" (47.5mm)	2.340" (59mm)
2 1/2"*	T2.5	2 1/2" Torquer	2.290" (58mm)	2.800" (71mm)
3"*	T3	3 1/2" Torquer	2.830" (72mm)	3.400" (86.5mm)
3 1/2"	T3.5	3 1/2" Torquer	3.400" (86mm)	3.750" (95mm)
4"	T4	4" Torquer	3.985" (98mm)	4.400" (112mm)
4 1/2"	T4.5	4 1/2" Torquer	4.400" (112mm)	4.750" (121mm)
4" 80	T4 80	4" Torquer	3.700" (94mm)	4.125" (105mm)
5"*	T5	5" Torquer	4.700" (119mm)	5.125" (132mm)
5 1/2"	T5.5	5 1/2" Torquer	5.400" (137mm)	5.750" (146mm)
6"*	T6	6" Torquer	5.725" (145mm)	6.350" (162mm)
6 1/2"	T6.5	6 1/2" Torquer	6.400" (163mm)	6.750" (171mm)
8"	T8	8" Torquer	TBA	TBA

* Size will also fit Sched. 80 pipe

