

24 Anchorage Connectors

Temporary Anchorage Connectors

Push-Thru Eye Bolt 420



This anchorage connector offers simple one-hand installation and can be used for a wide range of applications. Includes the integral SofStop Shock Absorber.

Wire Hook 470



Stainless steel wire hook connects to various anchorages including railings, small I-beams, angle iron and scaffolding. Simply squeeze the spring-loaded hook and slip the large opening over the approved structure.

Extension Pole & Hook 475



The extension pole and hook is ideal for climbing ladders and towers. Installs fall arrest systems up to 20 feet (6m) from ground level to angle iron, piping and related structures.

Rebar Hook Anchors 480/485



480



485

Designed to facilitate anchoring to scaffolding, pipe or angle iron, this anchor features a locking rebar hook for easy, one-hand installation and a D-ring on the other end to accommodate the connecting device.

Rebar Hook Anchor with SofStop Shock Absorber

Cross-Arm Strap 8183



The Miller cross-arm strap wraps around I-beams and other structures forming a secure attachment point for lanyards and other connecting devices.

Beam Trolleys 8804/9065



New

9065



8804

Miller beam trolleys are adjustable to fit different size I-beams and slide along with the worker to provide maximum mobility. The new lightweight beam trolley with retrofit kit adjusts to fit beam flanges from 3 inches (76mm) to 8-1/2 inches (216mm) wide.

Carabiners 17D-1/17D-2, 18D-1/18D-2



17D-1

Convenient, twist-lock carabiners have an unlimited number of uses.

Steel Carabiner
1" (25mm)
gate opening



New

17D-2

Lightweight Aluminum Carabiner
1" (25mm)
gate opening



18D-1

Steel Carabiner
2" (50mm)
gate opening



New

18D-2

Lightweight Aluminum Carabiner
2-1/4" (57mm)
gate opening



475

Miller Temporary Anchorage Connectors

Model Number	Product	Description	Occupations/ Applications
420	Push-Thru Eye Bolt	Spring-action anchorage connector fits 3/4" (19mm) diameter holes; features SofStop shock absorber	U
470	Wire Hook	Stainless steel, spring-loaded wire hook	U
475	Extension Pole & Hook	20' (6m) extension pole with spring-loaded hook	U
480	Rebar Hook Anchor	Locking rebar hook (w/2-1/2" (63mm) throat opening) and D-ring connected w/2" (50mm) nylon webbing	U
485	Rebar Hook Anchor	Same as Model 480 except includes the integral SofStop shock absorber	U
440	Cross-Arm Chain	6' (1.8m) chain with an oval ring on each end	U
8183	Cross-Arm Strap	2" (50mm) nylon webbing strap features a 2" (50mm) D-ring which slips through a 3" (76mm) D-ring	U
8185	Looped Cross-Arm Strap	2" (50mm) nylon webbing strap features a 2" (50mm) D-ring which slips through looped webbing	U
450	Beam Clamp	Steel clamp designed for attachment to horizontal I-beams, S-beams & W-beams up to 9" (229mm) wide; features swivel attachment ring for connecting devices	U
455	Beam Clamp	Same as Model 450 except that it accommodates beams up to 12-1/2" (317mm) wide	U
8804	Beam Trolley	Steel, sliding beam trolley accommodates I-beams from 3" (76mm) to 8" (203mm) wide	U
9065	Beam Trolley	Steel, sliding beam trolley accommodates I-beams up to 4-1/2" (114mm) wide; load rating up to 400 lbs. (1.8kN)	U
9065-1	Beam Trolley Retrofit Kit	Retrofit kit used w/model 9065 accommodates I-beams up to 8-1/2" (216mm) wide	U
16D-1	Screw-Lock Carabiner	Steel screw-lock carabiner w/1" (25mm) throat opening	U
17D-1	Twist-Lock Carabiner	Steel twist-lock carabiner w/1" (25mm) throat opening	U
17D-2	Twist-Lock Carabiner	Lightweight, aluminum twist-lock carabiner w/1" (25mm) throat opening	U
17D-3	Triple-Action Twist-Lock Carabiner	Lightweight, aluminum, triple-action twist-lock carabiner w/1" (25mm) throat opening	U
18D-1	Large Twist-Lock Carabiner	Steel twist-lock carabiner w/2" (50mm) throat opening	U
18D-2	Large Twist-Lock Carabiner	Lightweight, aluminum twist-lock carabiner w/2-1/4" (57mm) throat opening	U