## Miller® Rope Grabs & Vertical Lifelines

## Miller Rope Grabs

Miller Rope Grabs move easily up and down vertical lifelines to provide continuous fall protection. Trailing models offer complete hands-free operation for increased productivity.

In the event of a fall, Miller Rope Grabs lock instantly.

Corrosion-resistant stainless steel construction









8174

8175SLS

Model Number	Description	Occupations/ Applications					
8172*	Stainless steel, compact, trailing wire rope grab w/5/16" (8mm) wire rope tunnel	7	~	M	Ĩ.	<b>Alle</b>	緻
8173	Stainless steel, compact trailing rope grab w/5/8" (16mm) rope tunnel	7	~	M	Ĩ.	<b>M</b>	
8174	Stainless steel, manual rope grab w/ 5/8" (16mm) or 3/4" (19mm) synthetic rope tunnel	7	~	M	Ĩ.	<b>M</b>	
8174MLS	Same as 8174 except w/attached 4' (1.2m) Manyard shock-absorbing lanyard w/locking snap hook	7	<b>~</b>	×	<u></u>	<b>All</b>	
8174RLS	Same as 8174 except w/attached 2' (.6m) rope lanyard w/locking snap hook	7	~	M	<u> </u>	<b>Aller</b>	
8174WLS	Same as 8174 except w/attached 2' (.6m) nylon web lanyard w/locking snap hook	7	~	M	Ĩ.	<b>M</b>	图
98174LS	Same as 8174 except w/attached SofStop shock-absorber w/locking snap hook	7	~	M	Ĩ.	<b>Alle</b>	
8175	Stainless steel trailing rope grab w/5/8" (16mm) rope tunnel	7	~	M	Ĩ.	<b>M</b>	A
8175RLS	Same as 8175 except w/attached 3' (1m) rope lanyard w/locking snap hook	7	<b>~</b>	M	Ĩ.	<b>M</b>	
8175WLS	Same as 8175 except w/attached 3' (1m) nylon web lanyard w/locking snap hook	7	~	M	Ĩ.	<b>M</b>	
8175SLS	Same as 8175WLS except w/SofStop shock-absorber w/locking snap hook	7	<b>~</b>	M	<u></u>	Alle	

<sup>\*</sup>Does not meet CSA requirements

Miller rope grabs meet all applicable **OSHA**, **ANSI**, **P** Z259.2.1-98 and **(** requirements.

## Miller Vertical Lifelines

Rope grabs are to be used with 5/8 inch (16mm) or 3/4 inch (19mm) synthetic rope lifeline with a minimum tensile strength of 5,000 pounds (22kN), secured to an anchorage independent of the worker's platform. Standard lifeline lengths are 25 ft. (7.6m), 50 ft. (15m), 75 ft. (23m), and 100 ft. (30m); additional lengths are available. Wire rope grabs are to be used with 5/16 inch (8mm) galvanized or stainless steel wire rope lifelines.

Model Number*	Description		
194R-2	Nylon rope lifeline with carabiner and thimble; 5/8" (16mm) diameter		
194R-5	Polyester rope lifeline with carabiner and thimble; 5/8" (16mm) diameter		
195R-2	Nylon rope lifeline with thimbles; 5/8" (16mm) diameter		
195R-5	Polyester rope lifeline with thimbles; 5/8" (16mm) diameter		
300L	Polyester/polypropylene blend rope lifeline with locking snap hook and loop; 5/8" (16mm) diameter		

