





















Miller Lanyards With SofStop Shock Absorber

The versatile Miller SofStop Shock Absorber pack is available as an integral component of various Miller brand rope, wire rope and web lanyards.

Miller Lanyards with SofStop Shock Absorber

Model Number	Material	Number of Legs	Harness Connection	Anchorage Connection	Lanyard Length***	Special Features	Occupations/Applications
928LS	–	N/A	Locking snap hook	D-ring	18" (457mm)	–	
901RLS*	Rope	One	Locking snap hook	Locking snap hook	6' (1.8m)		
903RLS*	Rope	One	Locking snap hook	Locking snap hook	4' (1.2m) to 6' (1.8m)	Adjustable	
907LS	Wire rope	One	Locking snap hook	Locking snap hook	6' (1.8m)	–	  
907NLS	Vinyl-coated wire rope	One	Locking snap hook	Locking snap hook	6' (1.8m)	–	  
910WLS**	Nylon webbing	One	Locking snap hook	Locking snap hook	4' (1.2m) to 6' (1.8m)	Adjustable	
913WLS**	Nylon webbing	One	Locking snap hook	Locking snap hook	6' (1.8m)	–	
940WLS**	Nylon webbing	One	Locking snap hook	Locking snap hook	6' (1.8m)	Dbl. SofStop pk.	
8798-6**	Nylon webbing	Two	Locking snap hook	Locking snap hooks	6' (1.8m)	–	  
8798-6R**	Nylon webbing	Two	Locking snap hook	Locking rebar hooks	6' (1.8m)	–	    

*Available in nylon or polyester rope. To order nylon, add "-2" to the corresponding model number. (Ex.: 901RLS-2)

To order polyester, add "-5" to the corresponding model number. (Ex.: 903RLS-5)

**Also available in polyester webbing. To order, add a "D" after the "W" in the corresponding model number. (Ex.: 910WLS becomes 910WDLS)

***Available in lengths from 4' (1.2m) to 10' (3m).

Miller brand lanyards meet all applicable OSHA, ANSI and  requirements.



928LS



901RLS



903RLS



907LS



907NLS



910WLS



913WLS

940WLS

8798-6

8798-6R