

## Versatile, Shock-Absorbing Lanyard Designs

### Tubular Shock-Absorbing

**Lanyards** feature a built-in woven inner core which smoothly expands 3-1/2 feet (1.1m) to reduce fall arrest forces, while the outer jacket serves as a back-up web lanyard.

### Pack-Type Shock-Absorbing

**Lanyards** include the shock absorber pack as an integral part of a standard lanyard. In the event of a fall, the pack expands 3-1/2 feet (1.1m) to reduce fall forces while a back-up safety strap deploys for added fall protection.

- **Lightweight, durable polyester webbing**
- **Two-legged models available for continuous tie-off**
- **Locking snap and rebar hooks**

### SELECT THE PROPER FALL PROTECTION EQUIPMENT

#### Shock-Absorbing Lanyard or Self-Retracting Lifeline?

Calculate your Potential Fall Distance from the charts on the back cover.

## Titan Shock-Absorbing Lanyards



Model T5111



Model T5121



Model T5112



Model T5113



Model T5122



Model T6111



Model T6121



Model T6122

## Titan Shock-Absorbing Lanyards

Model No.	Webbing	Shock-Absorber Type	Number of Legs	Harness Connection	Anchorage Connection	Lanyard Length
<b>T5011</b>	Polyester	Built-In Core	One	Choke-Off Loop	Locking Snap Hook	6 ft. (1.8m)
<b>T5111</b>	Polyester	Built-In Core	One	Locking Snap Hook	Locking Snap Hook	6 ft. (1.8m)
<b>T5112</b>	Polyester	Built-In Core	One	Locking Snap Hook	Locking Rebar Hook (2-1/4" gate opening)	6 ft. (1.8m)
<b>T5113</b>	Polyester	Built-In Core	One	Locking Snap Hook	Locking Rebar Hook (1-3/4" gate opening)	6 ft. (1.8m)
<b>T5121</b>	Polyester	Built-In Core	Two	Locking Snap Hook	Locking Snap Hooks	6 ft. (1.8m)
<b>T5122</b>	Polyester	Built-In Core	Two	Locking Snap Hook	Locking Rebar Hooks (2-1/4" gate opening)	6 ft. (1.8m)
<b>T5123</b>	Polyester	Built-In Core	Two	Locking Snap Hook	Locking Rebar Hooks (1-3/4" gate opening)	6 ft. (1.8m)
<b>T6111</b>	Polyester	Pack-Type	One	Locking Snap Hook	Locking Snap Hook	6 ft. (1.8m)
<b>T6111V</b>	Polyester	Pack-Type	One	Locking Snap Hook	Locking Snap Hook	4 ft.-6 ft. (1.2m-1.8m) adjustable
<b>T6112</b>	Polyester	Pack-Type	One	Locking Snap Hook	Locking Rebar Hook (2-1/4" gate opening)	6 ft. (1.8m)
<b>T6112V</b>	Polyester	Pack-Type	One	Locking Snap Hook	Locking Rebar Hook (2-1/4" gate opening)	4 ft.-6 ft. (1.2m-1.8m) adjustable
<b>T6113</b>	Polyester	Pack-Type	One	Locking Snap Hook	Locking Rebar Hook (1-3/4" gate opening)	6 ft. (1.8m)
<b>T6121</b>	Polyester	Pack-Type	Two	Locking Snap Hook	Locking Snap Hooks	6 ft. (1.8m)
<b>T6122</b>	Polyester	Pack-Type	Two	Locking Snap Hook	Locking Rebar Hooks (2-1/4" gate opening)	6 ft. (1.8m)
<b>T6123</b>	Polyester	Pack-Type	Two	Locking Snap Hook	Locking Rebar Hooks (1-3/4" gate opening)	6 ft. (1.8m)

Standard length is 6 feet (1.8m).

Tubular shock-absorbing lanyards also available in lengths from 4 feet (1.2m) to 10 feet (3m).

Pack-type shock-absorbing lanyards also available in lengths from 3 feet (.9m) to 10 feet (3m).

Locking snap hook – 3/4" inch (19mm) gate opening; Locking rebar hooks – 2-1/4" (57mm) gate opening or 1-3/4" (44mm) gate opening.