

FIELD Environmental Instruments

Equipment Rental and Field Supplies

OAKTON

"Your Needs Are Our Business"

**Toll-Free
800-393-4009**

T-100 Turbidity Meter



The OAKTON T-100 turbidity meter is easy to calibrate-meter automatically prompts you to the next calibration standard. The large custom LCD displays reading and units of measure. Other features include auto-off, diagnostic error messages, and auto-ranging function. Power saving function lets you take over 1000 readings on a single set of AAA batteries. Sealed optical system with infrared light source delivers high accuracy across entire range.

What's included: meter, four primary standards (0.02, 20.0, 100 and 800 NTU), two empty cuvettes with light shield caps, 4 AAA batteries, instructions, and hard carrying case.

Waterproof and dustproof with IP67 rated housing that floats!
Four point push-button calibration for full-range accuracy
Auto-ranging from 0 to 1000 NTU

SPECIFICATIONS

Range	0 to 19.99 20.0 to 99.9 100 to 1000 NTU
Resolution	0.01 0.1 1
Accuracy	±2% of reading from 0 to 500 NTU ±3% of reading 500 to 1000 NTU
Light source	Infrared LED
Sample volume needed	10 mL
Response time	Less than 6 seconds
Operating temp range	0 to 50°C (32 to 122°F)
Display	7 segment LCD
Power	Four AAA alkaline batteries
Dimensions	6-1/2"L x 2-3/4"W x 2"H

99 Miller Avenue
Braddock, PA 15104

800-393-4009

Fax 412-271-5083

info@
fieldenvironmental.com

Visit us on the web
www.
fieldenvironmental.com

**Inquiries and
orders
800-393-4009**