

FIELD Environmental Instruments

Equipment Rental and Field Supplies

OAKTON

Portable pH/Con 10 Meter

"Your Needs Are Our Business"

Toll-Free
800-393-4009



Measure pH, conductivity and °C with one meter and probe! Meter includes versatile multi-sensor probe—there's no need to switch probes when you switch measurement modes.

Three point pH calibration with auto buffer recognition and 4 point conductivity calibration (one per range) provide high accuracy. Features include water-resistant membrane keypad, Auto-off, Hold, and ready indicator.

Features

- Switch from Conductivity to pH at the press of a button
- Replaceable Multi-sensor probe with 10ft submersible cable
- Dual display of pH (or conductivity) plus temperature
- Easy push-button conductivity and pH calibration
- Automatic Temperature Compensation (ATC)

SPECIFICATIONS

Temperature Compensation:	Automatic from 0 to 50°C
Conductivity Cell Constant (K):	1.0
Conductivity temperature coefficient:	2.00% per°C
Operating Temperature:	0 to 50°C
Power:	four 1.5 V AAA batteries
Battery Life:	>50 hours
Dimensions:	Meter -- 7.5"L x 3.5" W x 1.75"H Probe -- 6.8"L x 1.3" diameter
Shipping Weight:	1.4 lbs

TYPE	PH	CONDUCTIVITY	TEMPERATURE
Range	0 to 14.00 pH	0 to 19.99µS, 0 to 199.9µS, 0 to 1999µS, 0 to 19.99mS	0 to 100 °C
Resolution	0.01 pH	0.01µS, 0.1µS, 1µS, 0.01mS	0.1°C
Accuracy	± 0.01 pH	± 1% full scale or ±1 digit conductivity	± 0.5°C

99 Miller Avenue
Braddock, PA 15104
800-393-4009
Fax 412-271-5083

info@
fieldenvironmental.com

Visit us soon on the web
www.
fieldenvironmental.com

**Inquiries and
orders
800-393-4009**