

FIELD

Environmental Instruments

Equipment Rental and Field Supplies

Proactive

Power Booster II With Low Flow Controller

"Your Needs Are Our Business"



ORDERING INFORMATION

Toll-Free
800-393-4009

The Proactive Low Flow with Power Booster II Controller is engineered specifically for the Tsunami and Monsoon high performance pumps. This "Combo" Device will boost 12 volts to a constant 24 volts, thus maximizing purging efforts.

This device can also be used to achieve low flow sampling. In addition, this device can also be used to achieve low flow sampling. This controller lets the technician sample as low as 40ml/min. Finally, the technician now has the ability to either use this Controller to sample wells in accordance to EPA field sampling guidelines.

Simply hook the controller to a car battery and connect the pump to the Controller, turn on device with the on/off switch on the side... and stand back for awesome pumping power! And with the revolutionary variable speed dial, you have total control over the pumping volume.

Features:

- Heavy duty steel weatherproof case
- Low voltage disconnect at 11 volts
- 25 amp "safety" fuse to protect electronics and user
- Outstanding warranty includes 6 months parts and labor
- Low flow sampling dial
- Convenient on/off switch
- Three foot lead of battery connectors
- Steel handle for comfort grip

Field Environmental Instruments
301 Brushton Avenue, Suite A
Pittsburgh, PA 15221

For Orders or Inquiries:
800-393-4009
Fax 412-436-2616

Visit us on the web
www.fieldenvironmental.com