PROACTIVE ENVIRONMENTAL PRODUCTS-PROACTIVE PUMPS



The Mini-Typhoon pump is capable of pumping up to 40 feet from ground level to water level by simply connecting it to a 12 volt battery. Its reliable design is suitable for continuous sampling or purging of groundwater wells.

Simplify and Expedite Your Next Sampling Event!

The Mini-Typhoon can pass sand, small rocks and debris without getting clogged or damaging the pump motors!

The Mini-Typhoon can run continuously without the need for a cool down! Unlike, the competition.

The Mini-Typhoon can also run dry for up to two hours without motor damage!

The Mini-Typhoon has a 400 hour motor life! That is twice as long as the competition!

The Mini-Typhoon has a sleek outside that minimizes well hang-ups.

The Mini-Typhoon is a very reliable and economical pump that provides a great bang for your buck!

The Mini-Typhoon comes ready for field use; with 50 feet of heavy duty wire and alligator battery clamps and it is shipped in its own box.

SPECS:

SFECS.	
POWER CONSUMPTION:	105 WATTS (MAX)
VOLT RECOMMENDATION:	12 - 15 At Source
MAXIMUM AMP OUTPUT:	7 AMPS
MEASUREMENTS:	LENGTH 9.5" / DIAMETER: 1.8"
CONSTRUCTED:	PVC PLASTIC & STAINLESS STEEL
DISCHARGE OUTLET:	3/8" ID OR 1/2" ID POLY TUBING CAN BE USED
SUPPLIED WITH:	50 FEET OF HEAVY DUTY 12 GAUGE WIRE / BATTERY CLAMPS

Did you know??

The Mini-Typhoon can be used for Low Flow Sampling???





Mini-Typhoon Pump Chart		
PUMPING DEPTH (DTW)	GALLONS PER MINUTE	
3	2.5	
10	2.2	
20	2.0	
30	1.0	
40	.25	
50	N/A	