

MATERIAL SAFETY DATA SHEET

Prepared to U.S. OSHA, CMA, ANSI and Canadian WHMIS Standards

1. PRODUCT IDENTIFICATION

CHEMICAL NAME; CLASS: **HYDROGEN SULFIDE (1 PPM-4%)/METHANE (0-5%)/CARBON MONOXIDE (1 PPM-12.5%) /OXYGEN(0-22.5%)/NITROGEN (BALANCE) GAS MIXTURE**

CHEMICAL FAMILY: Organic Hydrocarbon Mixture

PRODUCT USE Calibration Mixture

MANUFACTURER

MATHESON TRI-GAS, INC.

959 ROUTE 46 EAST
PARSIPPANY, NJ 07054-0624
USA

Phone: 973/257-1100

EMERGENCY PHONE: **CHEMTREC (U.S. DOMESTIC):** **1-800-424-9300**
 CHEMTREC INTERNATIONAL: **1-703-527-3887**
 CANUTEC (CANADA): **1-613-996-6666**

2. COMPOSITION and INFORMATION ON INGREDIENTS

(10,000 ppm = 1%)

CHEMICAL NAME	CAS #	ppm	EXPOSURE LIMITS IN AIR					
			ACGIH-TLV		OSHA-STEL		NIOSH IDLH ppm	OTHER ppm
			TWA ppm	STEL ppm	TWA ppm	STEL ppm		
Hydrogen Sulfide	7783-06-4	1 ppm-4%	10 NIC = 5	15	10 (Vacated 1989 PEL)	20 (ceiling) 50 (ceiling), 10 min., peak, once per 8-hr shift 15 (Vacated 1989 PEL)	100	NIOSH REL: STEL = 10 (ceiling), 10 min. DFG MAKs: TWA = 10 PEAK = 2•MAK 15 min., average value, 1 hr interval
Methane	74-82-8	0-5%	NIC = 1000	Methane is a simple asphyxiant (SA). Oxygen levels should be maintained above 19.5%.				

NIC = Notice of Intended Change

NOTE: All WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-1998 format. This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

See Section 16 for Definitions of Terms Used.

HYDROGEN SULFIDE (1 ppm-4%)/METHANE (0-5%)/CARBON DIOXIDE (1 ppm-12.5%)/OXYGEN (0-22.5%)/ NITROGEN (Balance)GAS MIXTURE MSDS

2. COMPOSITION and INFORMATION ON INGREDIENTS (Continued)

(10,000 ppm = 1%)

CHEMICAL NAME	CAS #	ppm	EXPOSURE LIMITS IN AIR					
			ACGIH-TLV		OSHA-STEL		NIOSH IDLH ppm	OTHER ppm
			TWA ppm	STEL ppm	TWA ppm	STEL ppm		
Carbon Monoxide	630-08-0	1 ppm-12.5%	25	NE	50 35 (Vacated 1989 PEL)	200 (Vacated 1989 PEL)	1200	NIOSH RELs: TWA = 35 STEL = 200 (ceiling) DFG MAKs: TWA = 35 PEAK = 1•MAK, 15 min., average value, 1 hr interval DFG MAK Pregnancy Risk Classification: B
Oxygen	7782-44-7	0-22.5%	There are no specific exposure limits for Oxygen.					
Nitrogen	7727-37-9	Balance	There are no specific exposure limits for Nitrogen. Oxygen levels should be maintained above 19.5%.					

NIC = Noticed of Intended Change

NOTE: All WHMIS required information is included. It is located in appropriate sections based on the ANSI Z400.1-1998 format. This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

See Section 16 for Definitions of Terms Used.

3. HAZARD IDENTIFICATION

EMERGENCY OVERVIEW: This is a colorless, gas mixture, with a distinct "rotten egg" odor, due to the presence of Hydrogen Sulfide. Although this is a Nitrogen balance gas, the flammable components may be in concentration up to their LEL in air and since this mixture may contain the level of Oxygen present in air, the mixture must be viewed as flammable. This gas mixture can cause significant, adverse health effects at relatively low concentrations, due to the presence of Hydrogen Sulfide. Overexposure can cause dizziness, headache, nausea, respiratory arrest, coma, collapse or unconsciousness. Additionally, releases of this gas mixture may cause adverse effects on the central nervous system and/or produce oxygen-deficient atmospheres. Individuals in such atmospheres may be asphyxiated. Severe inhalation exposures may be fatal, due to Carbon Dioxide and Carbon Monoxide overexposure or asphyxiation. This gas mixture presents a serious fire hazard if accidentally released. Releases of this gas mixture will spread long distances; ignition or flash-back from a distance are possible. Flame or high temperature impinging on a localized area of the cylinder can cause cylinder to rupture violently or explosively. Provide adequate fire protection during emergency response.

SYMPTOMS OF OVER-EXPOSURE BY ROUTE OF EXPOSURE: The most significant route of over-exposure for this product is by inhalation. The components of this gas mixture that are not indicated to have specific health effects are either not known to have adverse health effects or there are no data regarding adverse effects.

HYDROGEN SULFIDE (1 ppm-4%)/METHANE (0-5%)/CARBON DIOXIDE (1 ppm-12.5%)/OXYGEN (0-22.5%)/NITROGEN (Balance)GAS MIXTURE MSDS

EFFECTIVE DATE: JULY 22, 2003

PAGE 2 OF 14

MATH0069

INHALATION: One of the components of this gas mixture, Hydrogen Sulfide, is toxic and can cause adverse effects at the concentrations present in this gas mixture. Inhalation of Hydrogen Sulfide can cause dizziness, headache, nausea, respiratory arrest, coma, or unconsciousness. Exposure to Hydrogen Sulfide for more than 30 minutes at concentrations of greater than 600 ppm have been fatal. Continuous inhalation of low concentrations may cause olfactory fatigue, so that the odor is no longer an effective warning of the presence of Hydrogen Sulfide.

3. HAZARD IDENTIFICATION (Continued)

INHALATION (continued): A summary of exposure concentrations and observed effects from Hydrogen Sulfide exposure are as follows:

CONCENTRATION
of HYDROGEN SULFIDE

EXPOSURE SYMPTOM

0.3-30 ppm:	Odor is obvious and unpleasant.
50 ppm:	Eye irritation. Dryness and irritation of nose, throat.
Slightly higher than 50 ppm:	Irritation of the respiratory system.
100-150 ppm:	Temporary loss of smell.
200-250 ppm:	Headache, vomiting, nausea. Prolonged exposure may lead to lung damage. Exposures of 4-8 hours can be fatal.
300-500 ppm:	Swifter onset of symptoms. Death occurs in 1-4 hours.
500 ppm:	Headache, excitement, staggering, stomach after brief exposure. Death occurs from 0.5 - 1 hour.
> 600 ppm:	Rapid onset of unconsciousness, coma, death.
> 1000 ppm:	Immediate respiratory arrest.

Severe exposures to Hydrogen Sulfide which do not result in death may cause long-term symptoms such as memory loss, paralysis of facial muscles, or nerve tissue damage.

Inhalation exposures may produce adverse health effects, due to the presence of Carbon Monoxide. Carbon Monoxide is classified as a chemical asphyxiant, producing a toxic action by combining with the hemoglobin of the blood and replacing the available oxygen. Since the affinity of Carbon Monoxide for hemoglobin is about 200-300 times that of oxygen, only a small amount of Carbon Monoxide will cause an adverse reaction to occur. Carbon Monoxide exposures in excess of 50 ppm will produce symptoms of poisoning if breathed for a sufficiently long time. If this gas mixture is inhaled, symptoms which may develop from Carbon Monoxide include those described below.

CARBON MONOXIDE

CONCENTRATION

OBSERVED EFFECT

All exposure levels:	Overexposure to Carbon Monoxide can be indicated by the lips and fingernails turning bright red.
200 ppm:	Slight symptoms (headache, discomfort) after several hours of exposure.
400 ppm:	Headache and discomfort experienced within 2-3 hours of exposure.
1000 to 2000 ppm:	Within 30 minutes, slight palpitations of the heart occur. Within 1.5 hours, there is a tendency to stagger. Within 2 hours, there is mental confusion, headache, and nausea.
2000-2500 ppm:	Unconsciousness within 30 minutes.
2500 ppm:	Potential for collapse and death before warning symptoms are produced.

In addition, high concentrations of this gas mixture can cause an oxygen-deficient environment, especially if released in a poorly-ventilated area (e.g., an enclosed or confined space). Individuals breathing such an atmosphere may experience symptoms which include headaches, ringing in ears, dizziness, drowsiness, unconsciousness, nausea, vomiting, and depression of all the senses. Under some circumstances of overexposure, death may occur. The effects associated with various levels of oxygen are as follows:

CONCENTRATION OF OXYGEN

OBSERVED EFFECT

12-16% Oxygen:	Breathing and pulse rate increase, muscular coordination slightly disturbed.
10-14% Oxygen:	Emotional upset, abnormal fatigue, disturbed respiration.
6-10% Oxygen:	Nausea, vomiting, collapse, or loss of consciousness.
Below 6%:	Convulsive movements, possible respiratory collapse, and death.

CONTACT WITH SKIN or EYES: The Hydrogen Sulfide component of this gas mixture, may be irritating to the skin. Inflammation and irritation of the eyes can occur at very low airborne concentrations (less than 10 ppm Hydrogen Sulfide). Exposure over several hours may result in "gas eyes" or "sore eyes" with symptoms of scratchiness, irritation, tearing and burning. Above 50 ppm, there is an intense tearing, blurring of vision, and pain when looking at light.

HYDROGEN SULFIDE (1 ppm-4%)/METHANE (0-5%)/CARBON DIOXIDE (1 ppm-12.5%)/OXYGEN (0-22.5%)/NITROGEN (Balance)GAS MIXTURE MSDS

3. HAZARD IDENTIFICATION (Continued)

CONTACT WITH SKIN or EYES (continued): Exposed individuals may see rings around bright lights. Most symptoms disappear when exposure ceases; however, in serious cases, the eye can be permanently damaged. In addition, contact with rapidly expanding gases (which are released under high pressure) may cause frostbite.

SKIN ABSORPTION: No component of this gas mixture presents a hazard of skin absorption.

HEALTH EFFECTS OR RISKS FROM EXPOSURE: Over-exposure to this gas mixture may cause the following health effects:

ACUTE: Due to the presence of Hydrogen Sulfide, inhalation of relatively low concentrations of this gas mixture can cause dizziness, headache, and nausea. Exposure to higher concentrations of this gas mixture can result in respiratory arrest, coma, and may be fatal due to the toxicity of Hydrogen Sulfide and oxygen deficiency. Continuous inhalation of low concentrations may cause olfactory fatigue, so that the odor of Hydrogen Sulfide is no longer an effective warning of over-exposure to this gas mixture. Symptoms of overexposure to Carbon Monoxide at concentrations present in this gas mixture, may include lips and fingernails turning bright red, headaches, shortness of breath, wheezing, blurred vision, memory loss, dizziness, indigestion, and nausea. Severe inhalation overexposures can be fatal. Additionally this gas mixture may cause skin and eye irritation.

CHRONIC: Severe exposures which do not result in death may cause long-term symptoms such as memory loss, paralysis of facial muscles, or nerve tissue damage. Carbon Monoxide is a reproductive toxin. Refer to Section 11 (Toxicological Information) of this MSDS for further information.

TARGET ORGANS: ACUTE: Respiratory system, skin, eyes, central nervous system. CHRONIC: Central nervous system, reproductive system.

HMIS RATING: HEALTH HAZARD = 2 FLAMMABILITY HAZARD = 4 PHYSICAL HAZARD = 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

4. FIRST-AID MEASURES

GENERAL INFORMATION: RESCUERS SHOULD NOT ATTEMPT TO RETRIEVE VICTIMS OF EXPOSURE TO THIS GAS MIXTURE WITHOUT ADEQUATE PERSONAL PROTECTIVE EQUIPMENT. At a minimum, Self-Contained Breathing Apparatus and Fire-Retardant clothing must be worn. Remove to fresh air, as quickly as possible. Only trained personnel should administer supplemental oxygen and/or cardio-pulmonary resuscitation, if necessary. Seek medical attention immediately.

SKIN EXPOSURE: Rinse exposed skin for 15 minutes if any irritation adverse effects occur. If release of this gas mixture has resulted in frostbite, warm affected area slowly. Seek immediate medical attention.

EYE EXPOSURE: If release of this gas mixture has affected the eyes, seek immediate medical attention.

THERMAL BURNS: In the event personnel are burned as a result of a release of this gas mixture, if burns are first degree or second degree with closed blisters, flush area with cold water until pain subsides. Apply loose, moist, sterile dressings, and bandage. Treat for shock. If burns are second degree with open blisters or third degree, apply loose, dry, sterile dressings and bandage. Treat for shock. Transport victim immediately to hospital or emergency center. Burns over an area of 20% or more of body are life-threatening, medical attention should be immediately sought.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing acute or chronic respiratory conditions may be aggravated by overexposure to this gas mixture.

RECOMMENDATIONS TO PHYSICIANS: Administer oxygen and continue even after spontaneous breathing is established. If pulmonary edema ensues, treat accordingly. In severe poisonings, treat with amyl nitrite and sodium nitrite as for cyanide poisoning, but omit sodium thiosulfate injection. Use of antibiotics should be considered at the first sign of pulmonary infection. Atropine sulfate may contribute some symptomatic relief. In event of eye contamination, conjunctivitis may be relieved by instillation of 1 drop of olive oil and sometimes by 3 to 4 drops of epinephrine solution (1:1000) at frequent intervals (e.g. 5 minutes). Occasionally, local anesthetics and hot or cold compresses are necessary to control pain.

5. FIRE-FIGHTING MEASURES

FLASH POINT: Not determined for mixture.

AUTOIGNITION TEMPERATURE: Not determined for mixture.

For Carbon Monoxide: 609°C (1128°F)

For Hydrogen Sulfide: 260°C (500°F)

For Methane: 537°C (999°F)

FLAMMABLE LIMITS (in air by volume, %): Not determined for mixture.

For Carbon Monoxide: LEL = 12.5% UEL = 74.0%

For Hydrogen Sulfide: LEL = 4.0% UEL = 44.0%

For Methane: LEL = 5.0% UEL = 15.0%

FIRE EXTINGUISHING MATERIALS: Extinguish fires of this gas mixture by shutting-off the source of gas. Use water spray to cool fire-exposed structures and equipment.

UNUSUAL FIRE AND EXPLOSION HAZARD: This gas is assumed to be flammable and may readily forms explosive mixtures with air over a very wide range. If released into a confined space, an extreme fire hazard exists.


EXPLOSION SENSITIVITY TO MECHANICAL IMPACT: Not sensitive.

EXPLOSION SENSITIVITY TO STATIC DISCHARGE: Static discharge may cause this gas mixture to ignite explosively.

SPECIAL FIRE-FIGHTING PROCEDURES: Evacuate all personnel from danger area. Immediately cool cylinders with water spray from maximum distance, taking care to NOT extinguish flames if source of gas has not been stopped. Stop the leak and flow of gas before extinguishing fire. If release is still occurring, explosive re-ignition may occur. In event that fire is extinguished before the leak is stopped, attempt to increase ventilation to area to prevent formation of explosive air/gas mixtures. Incipient fire responders should wear eye protection. Structural fire fighters must wear Self-Contained Breathing Apparatus and full protective equipment. When cool, move cylinders from fire area if this can be done without risk to firefighters. Other information for pre-planning can be found in the American Petroleum Institute Publications 2510 and 1510A, and the North American Emergency Response Guidebook (Guide Number 115).

Releases of this mixture which have not ignited must be considered extremely dangerous, and should not be approached.

NFPA RATING



**See Section 16 for
Definition of Ratings**

6. ACCIDENTAL RELEASE MEASURES

LEAK RESPONSE: Evacuate immediate area. Uncontrolled releases should be responded to by trained personnel using pre-planned procedures. Eliminate any possible source of ignition and provide maximum explosion-proof ventilation. Proper protective equipment, including fire protection, should be used in the event of a significant release from a single cylinder. Use only non-sparking tools. Call CHEMTREC (1-800-424-9300) for emergency assistance. Or if in Canada, call CANUTEC (613-996-6666).

Attempt to close the main source valve prior to entering the area. If this does not stop the release (or if it is not possible to reach the valve), allow the gas to release in-place or remove it to a safe area and allow the gas to be released there. Protect personnel attempting to shut-off with water spray. Monitor the surrounding area for combustible gas levels and the level of Oxygen. The atmosphere must have not more than 10% of the LEL of each component gas (see Section 5, Fire-Fighting Measures) and at least 19.5 percent Oxygen before non-emergency personnel can be allowed in the area without Self-Contained Breathing Apparatus and fire protection.

7. HANDLING and USE

WORK PRACTICES AND HYGIENE PRACTICES

Do not eat or drink while handling chemicals.

Be aware of all potential exposure symptoms; exposures to a fatal oxygen-deficient atmosphere could occur without any significant warning symptoms.

HYDROGEN SULFIDE (1 ppm-4%)/METHANE (0-5%)/CARBON DIOXIDE (1 ppm-12.5%)/OXYGEN (0-22.5%)/NITROGEN (Balance)GAS MIXTURE MSDS

7. HANDLING and USE (Continued)

WORK PRACTICES AND HYGIENE PRACTICES (continued):

All work operations should be monitored in such a way that emergency personnel can be immediately contacted in the event of a release.

Workers who handle this gas mixture should wear protective clothing, as listed in Section 8 (Exposure Controls and Personal Protection).

If ventilation controls are not adequate to provide sufficient oxygen content and to keep component levels below exposure limits given in Section 2 (Composition and Information on Ingredients), proper respiratory protection equipment should be provided and workers using such equipment should be carefully trained in its operation and limitations.

Precautions must always be taken to prevent suck-back of foreign materials into the cylinder by using a check-valve, or vacuum break, since suck-back may cause dangerous pressure changes within the cylinder.

STORAGE AND HANDLING PRACTICES:

Cylinders should be stored upright and be firmly secured to prevent falling or being knocked-over. Cylinders can be stored in the open, but in such cases, should be protected against extremes of weather and from the dampness of the ground to prevent rusting. Cylinders should be stored in dry, well-ventilated areas away from sources of heat or ignition. Do not allow the area where cylinders are stored to exceed 52°C (125°F).

Cylinders should be separated from oxygen cylinders, or other oxidizers, by a minimum distance of 20 ft., or by a barrier of non-combustible material at least 5 ft. high, having a fire-resistance rating of at least 0.5 hours. Isolate from other incompatible chemicals (refer to Section 10, Stability and Reactivity). Storage areas must meet National Electrical Codes for Class 1 Hazardous Areas. Post "No Smoking or Open Flames" signs in storage or use areas. Consider leak detection and alarm for storage and use areas. Have appropriate extinguishing equipment in storage area (i.e. sprinkler system, portable fire extinguishers).

SPECIAL PRECAUTIONS FOR HANDLING GAS CYLINDERS: Compressed gases can present significant safety hazards. The following rules are applicable to work situations in which cylinders are being used.

Before Use: Move cylinders with a suitable hand-truck. Do not drag, slide or roll cylinders. Do not drop cylinders or permit them to strike each other. Secure cylinders firmly. Leave the valve protection cap (where provided) in-place until cylinder is ready for use.

During Use: Use designated CGA fittings and other support equipment. Do not use adapters. Do not use oils or grease on gas-handling fittings or equipment. Immediately contact the supplier if there are any difficulties associated with operating the cylinder valve. Never insert an object (e.g wrench, screwdriver, pry bar, etc.) into valve cap openings. Doing so may damage the valve, causing a leak to occur. Use an adjustable strap wrench to remove over-tight or rusted caps. Never strike an arc, on a compressed gas cylinder or make a cylinder part of an electric circuit.

After Use: Close main cylinder valve. Replace valve protection cap. Close valve after each use and when empty. Mark empty cylinders "EMPTY".

PROTECTIVE PRACTICES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT: Refer to current CGA Guidelines for information on protective practices during maintenance of contaminated equipment.

8. EXPOSURE CONTROLS - PERSONAL PROTECTION

VENTILATION AND ENGINEERING CONTROLS: Use with adequate, explosion-proof ventilation to ensure compliance with exposure limits described in Section 2 (Composition and Information on Ingredients). Local exhaust ventilation is preferred, because it prevents dispersion of this gas mixture into the work place by eliminating it at its source. If appropriate, install automatic monitoring equipment to detect the level of Oxygen and the presence of potentially explosive air-gas mixtures.

RESPIRATORY PROTECTION: Maintain the Oxygen level above 19.5% in the workplace and levels of other components below the exposure limits given in Section 2 (Composition and Information on Ingredients). If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), or equivalent U.S. State standards and Canadian CSA Standard Z94.4-93. Oxygen levels below 19.5% are considered IDLH by OSHA. In such atmospheres, use of a full-facepiece

HYDROGEN SULFIDE (1 ppm-4%)/METHANE (0-5%)/CARBON DIOXIDE (1 ppm-12.5%)/OXYGEN (0-22.5%)/NITROGEN (Balance)GAS MIXTURE MSDS

pressure/demand SCBA or a full facepiece, supplied air respirator with auxiliary self-contained air supply is required under OSHA's Respiratory Protection Standard (1910.134-1998). (continued on next page)

8. EXPOSURE CONTROLS - PERSONAL PROTECTION (Continued)

RESPIRATORY PROTECTION (continued): The following are NIOSH respiratory protection guidelines for the Hydrogen Sulfide and Carbon Monoxide components of this gas mixture. These are presented as these components presents a risk of toxicity in this mixture.

CARBON MONOXIDE

CONCENTRATION

Up to 350 ppm:

Up to 875 ppm:

Up to 1200 ppm:

RESPIRATORY EQUIPMENT

Supplied Air Respirator (SAR).

SAR operated in a continuous flow mode.

Gas mask with canister to protect against carbon monoxide; or full-facepiece Self-Contained Breathing Apparatus (SCBA); or full-facepiece SAR.

Emergency or Planned Entry into Unknown Concentration or IDLH Conditions: Positive pressure, full-facepiece SCBA; or positive pressure, full-facepiece SAR with an auxiliary positive pressure SCBA.

Escape: Gas mask with canister to protect against carbon monoxide; or escape-type SCBA.

HYDROGEN SULFIDE

CONCENTRATION

Up to 100 ppm:

RESPIRATORY PROTECTION

Any Powered, Air-Purifying Respirator (PAPR) with cartridge(s), or any Air-Purifying, Full-Facepiece Respirator (gas mask) with a chin-style, front- or back-mounted canister, or any Supplied-Air Respirator (SAR), or any Self-Contained Breathing Apparatus (SCBA) with a full facepiece.

Emergency or Planned Entry Into Unknown Concentrations or IDLH Conditions: Any SCBA that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode, or any SAR that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary SCBA operated in pressure-demand or other positive-pressure mode.

Escape: Any Air-Purifying, Full-Facepiece Respirator (gas mask) with a chin-style, front- or back-mounted canister providing protection against the compound of concern, or any appropriate escape-type, SCBA.

EYE PROTECTION: Splash goggles or safety glasses. If necessary, refer to U.S. OSHA 29 CFR 1910.133, or appropriate Canadian Standards.

HAND PROTECTION: Wear mechanically-resistant gloves when handling cylinders containing this gas mixture. If necessary, refer to U.S. OSHA 29 CFR 1910.138, or appropriate Standards of Canada.

BODY PROTECTION: Use body protection appropriate for task. Transfer of large quantities under pressure may require protective equipment appropriate to the task. If a hazard of injury to the feet exists due to falling objects, rolling objects, where objects may pierce the soles of the feet or where employee's feet may be exposed to electrical hazards, foot protection should be used, as described in U.S. OSHA 29 CFR 1910.136.

9. PHYSICAL and CHEMICAL PROPERTIES

The following information is for Nitrogen, the main component of this gas mixture:

VAPOR DENSITY: 1.145 kg/m³ (0.0715 lb/ft³)

SPECIFIC GRAVITY (air = 1): 0.967

SOLUBILITY IN WATER: 1.49% (v/v)

EXPANSION RATIO: Not applicable.

ODOR THRESHOLD: Not applicable.

COEFFICIENT WATER/OIL DISTRIBUTION: Not applicable.

EVAPORATION RATE (nBuAc = 1): Not applicable.

FREEZING POINT: -210°C (-345.8°F)

BOILING POINT(@ 1 atmos.): -195.8°C (-320.4°F)

SPECIFIC VOLUME (ft³/lb): 13.8

VAPOR PRESSURE (psia): Not applicable.

The following information is pertinent to this product:

APPEARANCE, ODOR AND COLOR: This gas mixture is colorless and has a distinct "rotten egg" smell due to the presence of Hydrogen Sulfide.

HOW TO DETECT THIS SUBSTANCE (warning properties): The smell of this gas mixture cannot be relied upon as an adequate warning of a release as the Hydrogen Sulfide component causes olfactory

HYDROGEN SULFIDE (1 ppm-4%)/METHANE (0-5%)/CARBON DIOXIDE (1 ppm-12.5%)/OXYGEN (0-22.5%)/NITROGEN (Balance)GAS MIXTURE MSDS

EFFECTIVE DATE: JULY 22, 2003

fatigue after continuous exposure to low concentration. In terms of leak detection, fittings and joints can be painted with a soap solution to detect leaks, which will be indicated by a bubble formation.

10. STABILITY and REACTIVITY

STABILITY: Stable at standard temperatures and pressures.

DECOMPOSITION PRODUCTS: The decomposition products for individual components are as follows:

Hydrogen Sulfide decomposes to form water and sulfur oxide.

Methane decompose to form oxides of nitrogen when ignited.

Nitrogen does not decompose, per se, but may react with other compounds in the heat of a fire.

MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: The Carbon Monoxide component is incompatible with acrolein, aziridine, magnesium, titanium, zirconium, sodium peroxide, powders of aluminum, magnesium and tin, diethyl magnesium, cesium oxide, monolithium acetylide-ammonia, rubidium acetylides, lithium, sodium and metal hydrides. The Hydrogen Sulfide component of this gas mixture, is a strong reducing agent and may also react with alkaline materials, metals (e.g., copper, lead, silver), and metal oxides, even in relatively low concentrations. The Methane component of this gas mixture is incompatible with strong oxidizers (i.e. chlorine, bromine, pentafluoride, oxygen difluoride, and nitrogen trifluoride). The Nitrogen component is inert. The Oxygen component of this gas mixture is not compatible with fuels or strong reducing agents.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Contact with incompatible materials. Cylinders exposed to high temperatures or direct flame can rupture or burst.

11. TOXICOLOGICAL INFORMATION

TOXICITY DATA: The Nitrogen and Methane components are simple asphyxiants (SA), which act to displace oxygen in the environment. No toxicity data are applicable. There are toxicity data for Oxygen, but they are relevant only in a hyperbaric environment and are not applicable to this gas mixture. The following are toxicity data for the Hydrogen Sulfide component of this gas mixture:

CARBON MONOXIDE:

LC₅₀ (Inhalation-Rat) 1807 ppm/ 4 hour s

LC₅₀ (Inhalation-Mouse) 2444 ppm/ 4 hours

TCLo (Inhalation-Human) 600 mg/m³/ 10 minutes

TCLo (Inhalation-Man) 650 ppm/45 minutes: Central nervous system, Blood effects

TCLo (Inhalation-Mouse) 65 ppm/ 24 hours (female 7–18 days post): Reproductive effects

TCLo (Inhalation-Mouse): 8 pph/ 1 hours (female 8 days post): Teratogenic effects

LCLo (Inhalation-Man) 4000 ppm/ 30 minutes

LCLo (Inhalation-Human) 5000 ppm/ 5 minutes

HYDROGEN SULFIDE:

LCLo (Inhalation-Human) 600 ppm/30 minutes

LCLo (Inhalation-Man) 5700 µg/kg: Behavioral: coma; Lungs, Thorax, or Respiration: chronic pulmonary edema

LCLo (Inhalation-Human) 800 ppm/5 minutes

LCLo (Inhalation-Mammal-species unspecified) 800 ppm/5 minutes

LC₅₀ (Inhalation-Rat) 444 ppm: Lungs, Thorax, or Respiration: other changes; Gastrointestinal: hypermotility, diarrhea; Kidney, Ureter, Bladder: urine volume increased

LC₅₀ (Inhalation-Mouse) 634 ppm/1 hour

HYDROGEN SULFIDE (continued):

TCLo (Inhalation-Rat) 30 ppm/6 hours/10 weeks-intermittent: Sense Organs and Special Senses (Olfaction): olfactory nerve change, effect, not otherwise specified

TCLo (Inhalation-Rat) 1200 mg/m³/2 hours/5 days-intermittent: Brain and Coverings: other degenerative changes; Biochemical: Enzyme inhibition, induction, or change in blood or tissue levels: true cholinesterase

TCLo (Inhalation-Rat) 100 ppm/8 hours/5 weeks-intermittent: Brain and Coverings: other degenerative changes; Lungs, Thorax, or Respiration: other changes; Biochemical: Enzyme inhibition, induction, or change in blood or tissue levels: cytochrome oxidases (including oxidative phosphorylation)

TCLo (Inhalation-Rat) 80 ppm/6 hours/90 days-intermittent: Brain and Coverings: changes in brain weight; Nutritional and Gross Metabolic: weight loss or decreased weight gain

TCLo (Inhalation-Rat) 20 ppm: female 6-22 day(s) after conception lactating female 21 day(s) post-birth: Reproductive: Effects on Newborn: physical

TCLo (Inhalation-Mouse) 80 ppm/6 hours/90 days-intermittent: Nutritional and Gross Metabolic: weight loss or decreased weight gain; Related to Chronic Data: death

TCLo (Inhalation-Rabbit) 40 mg/m³/5 hours/30 weeks-intermittent: Sense Organs and Special Senses (Eye): conjunctive irritation

SUSPECTED CANCER AGENT: The components of this gas mixture are not found on the following lists: FEDERAL OSHA Z LIST, IARC, NTP, CAL/OSHA, and therefore is not considered to be, nor suspected to be a cancer-causing agent by these agencies.

IRRITANCY OF PRODUCT: This gas mixture may be irritating to contaminated tissue, due to the presence of Hydrogen Sulfide.

HYDROGEN SULFIDE (1 ppm-4%)/METHANE (0-5%)/CARBON DIOXIDE (1 ppm-12.5%)/OXYGEN (0-22.5%)/ NITROGEN (Balance)GAS MIXTURE MSDS

EFFECTIVE DATE: JULY 22, 2003

11. TOXICOLOGICAL INFORMATION (Continued)

SENSITIZATION TO THE PRODUCT: The components of this product are not known to be skin or respiratory sensitizers.

REPRODUCTIVE TOXICITY INFORMATION: Listed below is information concerning the effects of the components of this gas mixture on the human reproductive system.

Mutagenicity: This gas mixture is not expected to cause mutagenic effects in humans. Animal mutagenic data are available for the Carbon Monoxide component of this gas mixture; these data were obtained during clinical studies on specific animal tissues exposed to relatively high doses of this gas.

Embryotoxicity: This gas mixture is not expected to cause embryotoxic effects in humans. Animal mutagenic data are also available for the Carbon Monoxide component of this gas mixture; these data were obtained during clinical studies on specific animal tissues exposed to relatively high doses of this gas.

Teratogenicity: This gas mixture contains a component that can cause teratogenic effects in humans, Carbon Monoxide.

Reproductive Toxicity: This gas mixture is not expected to cause adverse reproductive effects in humans. Animal reproductive data are available for the Hydrogen Sulfide component of this gas mixture at high doses.

BIOLOGICAL EXPOSURE INDICES (BEIs): There are Biological Exposure Indices (BEIs) determined for the Carbon Monoxide component of this gas mixture, as follows.

CHEMICAL DETERMINANT	SAMPLING TIME	BEI
CARBON MONOXIDE • Carboxyhemoglobin in Blood • Carbon monoxide in End-Exhaled Air	• End of Shift • End of Shift	• 3.5% of Hemoglobin • 20 ppm

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL STABILITY: This gas mixture will be dissipated rapidly in well-ventilated areas.

EFFECT OF MATERIAL ON PLANTS or ANIMALS: Any adverse effect on animals would be related to oxygen deficient environments.

EFFECT OF CHEMICAL ON AQUATIC LIFE: There are no data on possible adverse effects from this gas mixture on aquatic life. The following are aquatic toxicity data for the Hydrogen Sulfide component:

TLm (*Asellus* sp) 96 hours = 0.111 mg/L

TLm (*Ceriodaphnia dubia*) 96 hours = 1.07 mg/L

TLm (*Gambusia*) 96 hours = 0.84 mg/L

LC₅₀ (fly inhalation) 960 minutes = 380 mg/m³

LC₅₀ (fly inhalation) 7 minutes = 1500 mg/m³

TLm (*Lepomis macrochirus*, bluegill sunfish) 96 hours = 0.0478 mg/L

TLm (*Lepomis macrochirus*, bluegill sunfish) 96 hours = 0.0448 mg/L @ t 21-22°C

TLm (*Pimephales promelas*, fathead minnow) 96 hours = 0.0071-0.55 mg/L

TLm (*Salvelinus fontinalis*, brook trout) 96 hours = 0.0216-0.038 mg/L @ 8-12.5°C

13. DISPOSAL CONSIDERATIONS

PREPARING WASTES FOR DISPOSAL: Waste disposal must be in accordance with appropriate Federal, State, and local regulations. Return cylinders with any residual product to Matheson Tri-Gas. Do not dispose of locally.

HYDROGEN SULFIDE (1 ppm-4%)/METHANE (0-5%)/CARBON DIOXIDE (1 ppm-12.5%)/OXYGEN (0-22.5%)/NITROGEN (Balance)GAS MIXTURE MSDS

14. TRANSPORTATION INFORMATION

THIS GAS MIXTURE IS HAZARDOUS AS DEFINED BY 49 CFR 172.101 BY THE U.S. DEPARTMENT OF TRANSPORTATION.

PROPER SHIPPING NAME: Compressed gases, flammable, n.o.s. (Hydrogen Sulfide, Carbon Monoxide, Nitrogen) **or** (Hydrogen Sulfide, Carbon Monoxide, Oxygen, Nitrogen) **or** (Hydrogen Sulfide, Carbon Monoxide, Methane, Nitrogen) **or** (Hydrogen Sulfide, Carbon Monoxide, Methane, Nitrogen)

HAZARD CLASS NUMBER and DESCRIPTION: 2.1 (Flammable Gas)

UN IDENTIFICATION NUMBER: UN 1954

PACKING GROUP: Not applicable.

D.O.T HAZARD LABEL: Class 2.1 (Flammable Gas)

NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER (2000): 115

MARINE POLLUTANT: The components of this gas mixture are not classified by the DOT as a Marine Pollutants (as defined by 49 CFR 172.101, Appendix B).

SPECIAL SHIPPING INFORMATION: Cylinders should be transported in a secure position, in a well-ventilated vehicle. The transportation of compressed gas cylinders in automobiles or in closed-body vehicles present serious safety hazards and should be discouraged.

NOTE: Shipment of compressed gas cylinders which have not been filled with the owner's consent is a violation of Federal law [49 CFR, Part 173.301 (b)].

TRANSPORT CANADA TRANSPORTATION OF DANGEROUS GOODS REGULATIONS: This gas mixture is considered as dangerous goods, per regulations of Transport Canada.

PROPER SHIPPING NAME: Compressed gases, flammable, n.o.s. (Hydrogen Sulfide, Carbon Monoxide, Nitrogen) **or** (Hydrogen Sulfide, Carbon Monoxide, Oxygen, Nitrogen) **or** (Hydrogen Sulfide, Carbon Monoxide, Methane, Nitrogen) **or** (Hydrogen Sulfide, Carbon Monoxide, Methane, Nitrogen)

HAZARD CLASS NUMBER and DESCRIPTION: 2.1 (Flammable Gas)

UN IDENTIFICATION NUMBER: UN 1954

PACKING GROUP: Not Applicable

HAZARD LABEL: Class 2.1 (Flammable Gas)

SPECIAL PROVISIONS: 16

EXPLOSIVE LIMIT AND LIMITED QUANTITY INDEX: 0.12

ERAP INDEX: 3,000

PASSENGER CARRYING SHIP INDEX: Forbidden

PASSENGER CARRYING ROAD VEHICLE OR PASSENGER CARRYING RAILWAY VEHICLE INDEX:

NORTH AMERICAN EMERGENCY RESPONSE GUIDEBOOK NUMBER (2000): 115

NOTE: Shipment of compressed gas cylinders via Public Passenger Road Vehicle is a violation of Canadian law (Transport Canada Transportation of Dangerous Goods Act, 1992).

SPECIAL SHIPPING INFORMATION: Cylinders should be transported in a secure position, in a well-ventilated vehicle. The transportation of compressed gas cylinders in automobiles or in closed-body vehicles present serious safety hazards and should be discouraged.

NOTE: Shipment of compressed gas cylinders which have not been filled with the owner's consent is a violation of Federal law (49 CFR, Part 173.301 (b)).

15. REGULATORY INFORMATION

ADDITIONAL U.S. REGULATIONS:

U.S. SARA REPORTING REQUIREMENTS: The Hydrogen Sulfide component of this gas mixture is subject to the reporting requirements of Sections 302, 304 and 313 of Title III of the Superfund Amendments and Reauthorization Act, as follows:

CHEMICAL NAME	SARA 302 (40 CFR 355, Appendix A)	SARA 304 (40 CFR Table 302.4)	SARA 313 (40 CFR 372.65)
Hydrogen Sulfide	Yes	Yes	Yes

U.S. SARA SECTION 302 EXTREMELY HAZARDOUS THRESHOLD PLANNING QUANTITY (TPQ):

Hydrogen Sulfide = 500 lb (227 kg)

U.S. SARA SECTION 304 EXTREMELY HAZARDOUS REPORTABLE QUANTITY (RQ): Hydrogen Sulfide = 100 lb (45.47 kg)

U.S. SARA HAZARD CATEGORIES (SECTION 311/312, 40 CFR 370-21): ACUTE: Yes; CHRONIC: Yes; FIRE: No; REACTIVE: No; SUDDEN RELEASE: Yes

U.S. TSCA INVENTORY STATUS: Components of this product are listed on the TSCA Inventory.

U.S. CERCLA REPORTABLE QUANTITY (RQ): Hydrogen Sulfide = 100 lb (45.4 kg)

OTHER U.S. FEDERAL REGULATIONS: Hydrogen Sulfide and Methane are subject to the reporting requirements of Section 112(r) of the Clean Air Act. The threshold quantity for these gases is 10,000 lbs (4,540 kg). Hydrogen Sulfide is listed in Table 1, as a Regulated Substance (Toxic Substance) in quantities of 10,000 lb (4,553 kg) or greater. Methane is listed as a Regulated Substance in quantities of 10,000 lbs (4,540 kg) or greater, per 40 CFR, Part 68 of the Risk Management for Chemical Accidental Release. Any process that involves a flammable gas on-site, in one location, in quantities of 10,000 lbs (4,540 kg) or greater has requirements under the Process Safety Management of Highly Hazardous Chemicals (29 CFR 1910.119), unless the gas is used as a fuel.

U.S. STATE REGULATORY INFORMATION: Components of this product are covered under some specific State regulations, as denoted below (other State regulatory lists may exist; individual States should be contacted regarding full compliance).

California - Permissible Exposure Limits for Chemical Contaminants: Carbon Monoxide, Hydrogen Sulfide, Methane, Nitrogen.

New Jersey - Right to Know Hazardous Substance List: Carbon Monoxide, Hydrogen Sulfide, Methane, Nitrogen.

Pennsylvania - Hazardous Substance List: Carbon Monoxide, Hydrogen Sulfide, Methane, Nitrogen.

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65): The Carbon Monoxide is on the California Proposition List as a compound that causes reproductive toxicity. **WARNING!** This product contains a compound known to the State of California to cause reproductive harm.

LABELING: Cylinders of this gas mixture should be labeled for precautionary information per the guidelines of the CGA. Refer to the CGA for further information.


ADDITIONAL CANADIAN REGULATIONS:

CANADIAN DSL/NDL INVENTORY STATUS: The components of this product are listed on the DSL Inventory.

OTHER CANADIAN REGULATIONS: Not applicable.

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS: The components of this product are not on the CEPA Priorities Substances Lists.

CANADIAN WHMIS SYMBOLS: This gas mixture would be categorized as a Controlled Product, Hazard Classes: **A** (compressed gas), and **D1A** (Materials Causing Other Toxic Effects - Acute and Chronic Toxic Effects). The following symbol is required for WHMIS compliance for this gas mixture.



HYDROGEN SULFIDE (1 ppm-4%)/METHANE (0-5%)/CARBON DIOXIDE (1 ppm-12.5%)/OXYGEN (0-22.5%)/NITROGEN (Balance)GAS MIXTURE MSDS

16. OTHER INFORMATION

CREATION DATE: June 10, 2003

REVISION DATE: New

MIXTURES: When two or more gases or liquefied gases are mixed, their hazardous properties may combine to create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you use the mixture. Consult an Industrial Hygienist or other trained person when you make your safety evaluation of the end product. Remember, gases and liquids have properties which can cause serious injury or death.

Further information can be found in the following pamphlets published by: Compressed Gas Association Inc. (CGA), 1725 Jefferson Davis Highway, Suite 1004, Arlington, VA 22202-4102. Telephone: (703) 412-0900.

"Safe Handling of Compressed Gases in Containers" (P-1, 1999)

"Safe Handling and Storage of Compressed Gases" (AV-1, 1999)

"Handbook of Compressed Gases" (1992)

PREPARED BY:

CHEMICAL SAFETY ASSOCIATES, Inc.
PO Box 3519, La Mesa, CA 91944-3519
800/441-3365

DEFINITIONS OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these which are commonly used include the following:

CAS #: This is the Chemical Abstract Service Number that uniquely identifies each constituent.

EXPOSURE LIMITS IN AIR:

CEILING LEVEL: The concentration that shall not be exceeded during any part of the working exposure.

LOQ: Limit of Quantitation.

MAK: Federal Republic of Germany Maximum Concentration Values in the workplace.

NE: Not Established. When no exposure guidelines are established, an entry of NE is made for reference.

NIC: Notice of Intended Change.

NIOSH CEILING: The exposure that shall not be exceeded during any part of the workday. If instantaneous monitoring is not feasible, the ceiling shall be assumed as a 15-minute TWA exposure (unless otherwise specified) that shall not be exceeded at any time during a workday.

NIOSH RELs: NIOSH's Recommended Exposure Limits.

PEL-Permissible Exposure Limit: OSHA's Permissible Exposure Limits. This exposure value means exactly the same as a TLV, except that it is enforceable by OSHA.

The OSHA Permissible Exposure Limits are based in the 1989 PELs and the June, 1993 Air Contaminants Rule (Federal Register: 58: 35338-35351 and 58: 40191). Both the current PELs and the vacated PELs are indicated. The phrase, "Vacated 1989 PEL," is placed next to the PEL that was vacated by Court Order.

SKIN: Used when there is a danger of cutaneous absorption.

STEL-Short Term Exposure Limit: Short Term Exposure Limit, usually a 15-minute time-weighted average (TWA) exposure that should not be exceeded at any time during a workday, even if the 8-hr TWA is within the TLV-TWA, PEL-TWA or REL-TWA.

TLV-Threshold Limit Value: An airborne concentration of a substance that represents conditions under which it is generally believed that nearly all workers may be repeatedly exposed without adverse effect. The duration must be considered, including the 8-hour.

TWA-Time Weighted Average: Time Weighted Average exposure concentration for a conventional 8-hr (TLV, PEL) or up to a 10-hr (REL) workday and a 40-hr workweek.

IDLH-Immediately Dangerous to Life and Health: This level represents a concentration from which one can escape within

30-minutes without suffering escape-preventing or permanent injury.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM

HAZARD RATINGS: This rating system was developed by the National Paint and Coating Association and has been adopted by industry to identify the degree of chemical hazards.

HEALTH HAZARD:

0 (Minimal Hazard): No significant health risk, irritation of skin or eyes not anticipated. *Skin Irritation:* Essentially non-irritating. PII or Draize = "0".

HYDROGEN SULFIDE (1 ppm-4%)/METHANE (0-5%)/CARBON DIOXIDE (1 ppm-12.5%)/OXYGEN (0-22.5%)/NITROGEN (Balance)GAS MIXTURE MSDS

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM

HAZARD RATINGS (continued):

HEALTH HAZARD (continued):

0 (continued): *Eye Irritation:* Essentially non-irritating, or minimal effects which clear in < 24 hours [e.g. mechanical irritation]. Draize = "0". *Oral Toxicity LD₅₀ Rat:* < 5000 mg/kg. *Dermal Toxicity LD₅₀Rat or Rabbit* < 2000 mg/kg. *Inhalation Toxicity 4hrs LC₅₀ Rat:* < 20 mg/L.; **1** (Slight Hazard: Minor reversible Injury may occur; slightly or mildly irritating. *Skin Irritation:* Slightly or mildly irritating. *Eye Irritation:* Slightly or mildly irritating. *Oral Toxicity LD₅₀ Rat:* > 500-5000 mg/kg. *Dermal Toxicity LD₅₀Rat or Rabbit* > 1000-2000 mg/kg. *Inhalation Toxicity LC₅₀ 4-hrs Rat:* > 2-20 mg/L); **2** (Moderate Hazard: Temporary or transitory injury may occur. *Skin Irritation:* Moderately irritating; primary irritant; sensitizer. PII or Draize > 0, < 5. *Eye Irritation:* Moderately to severely irritating and/or corrosive; reversible corneal opacity; corneal involvement or irritation clearing in 8-21 days. Draize > 0, ≤ 25. *Oral Toxicity LD₅₀ Rat:* > 50-500 mg/kg. *Dermal Toxicity LD₅₀Rat or Rabbit* > 200-1000 mg/kg. *Inhalation Toxicity LC₅₀ 4-hrs Rat:* > 0.5-2 mg/L.); **3** (Serious Hazard: Major injury likely unless prompt action is taken and medical treatment is given; high level of toxicity; corrosive. *Skin Irritation:* Severely irritating and/or corrosive; may destroy dermal tissue, cause skin burns,

dermal necrosis. PII or Draize > 5-8 with destruction of tissue. *Eye Irritation:* Corrosive, irreversible destruction of ocular tissue; corneal involvement or irritation persisting for more than 21 days. Draize > 80 with effects irreversible in 21 days. *Oral Toxicity LD₅₀ Rat:* > 1-50 mg/kg. *Dermal Toxicity LD₅₀Rat or Rabbit* > 20-200 mg/kg. *Inhalation Toxicity LC₅₀ 4-hrs Rat:* > 0.05-0.5 mg/L.); **4** (Severe Hazard: Life-threatening; major or permanent damage may result from single or repeated exposure. *Skin Irritation:* Not appropriate. Do not rate as a "4", based on skin irritation alone. *Eye Irritation:* Not appropriate. Do not rate as a "4", based on eye irritation alone. *Oral Toxicity LD₅₀ Rat:* ≤ 1 mg/kg. *Dermal Toxicity LD₅₀Rat or Rabbit* ≤ 20 mg/kg. *Inhalation Toxicity LC₅₀ 4-hrs Rat:* ≤ 0.05 mg/L).

FLAMMABILITY HAZARD:

0 (Minimal Hazard-Materials that will not burn in air when exposure to a temperature of 815.5°C [1500°F] for a period of 5 minutes.); **1** (Slight Hazard-Materials that must be pre-heated before ignition can occur. Material require considerable pre-heating, under all ambient temperature conditions before ignition and combustion can occur, Including: Materials that will burn in air when exposed to a temperature of 815.5°C (1500°F) for a period of 5 minutes or less; Liquids, solids and semisolids having a flash point at or above 93.3°C [200°F] (e.g. OSHA Class IIIB, or; Most ordinary combustible materials [e.g. wood, paper, etc.];

16. OTHER INFORMATION (Continued)

DEFINITIONS OF TERMS (Continued)

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM HAZARD RATINGS (continued):

FLAMMABILITY HAZARD (continued):

2 (Moderate Hazard-Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur. Materials in this degree would not, under normal conditions, form hazardous atmospheres in air, but under high ambient temperatures or moderate heating may release vapor in sufficient quantities to produce hazardous atmospheres in air, including: Liquids having a flash-point at or above 37.8°C [100°F]; Solid materials in the form of course dusts that may burn rapidly but that generally do not form explosive atmospheres; Solid materials in a fibrous or shredded form that may burn rapidly and create flash fire hazards (e.g. cotton, sisal, hemp; Solids and semisolids that readily give off flammable vapors.); **3** (Serious Hazard- Liquids and solids that can be ignited under almost all ambient temperature conditions. Materials in this degree produce hazardous atmospheres with air under almost all ambient temperatures, or, unaffected by ambient temperature, are readily ignited under almost all conditions, including: Liquids having a flash point below 22.8°C [73°F] and having a boiling point at or above 38°C [100°F] and below 37.8°C [100°F] [e.g. OSHA Class IB and IC]; Materials that on account of their physical form or environmental conditions can form explosive mixtures with air and are readily dispersed in air [e.g., dusts of combustible solids, mists or droplets of flammable liquids]; Materials that burn extremely rapidly, usually by reason of self-contained oxygen [e.g. dry nitrocellulose and many organic peroxides]); **4** (Severe Hazard-Materials that will rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air, and which will burn readily, including: Flammable gases; Flammable cryogenic materials; Any liquid or gaseous material that is liquid while under pressure and has a flash point below 22.8°C [73°F] and a boiling point below 37.8°C [100°F] [e.g. OSHA Class IA; Material that ignite spontaneously when exposed to air at a temperature of 54.4°C [130°F] or below [e.g. pyrophoric]).

PHYSICAL HAZARD:

0 (*Water Reactivity*: Materials that do not react with water. *Organic Peroxides*: Materials that are normally stable, even under fire conditions and will not react with water. *Explosives*: Substances that are Non-Explosive. *Unstable Compressed Gases*: No Rating. *Pyrophorics*: No Rating. *Oxidizers*: No "0" rating allowed. *Unstable Reactives*: Substances that will not polymerize, decompose, condense or self-react.); **1** (*Water Reactivity*: Materials that change or decompose upon exposure to moisture. *Organic Peroxides*: Materials that are normally stable, but can become unstable at high temperatures and pressures. These materials may react with water, but will not release energy. *Explosives*: Division 1.5 & 1.6 substances that are very insensitive explosives or that do not have a mass explosion hazard. *Compressed Gases*: Pressure below OSHA definition. *Pyrophorics*: No Rating. *Oxidizers*: Packaging Group III; Solids: any material that in either concentration tested, exhibits a mean burning time less than or equal to the mean burning time of a 3:7 potassium bromate/cellulose mixture and the criteria for Packing Group I and II are not met. Liquids: any material that exhibits a mean pressure rise time less than or equal to the pressure rise time of a 1:1 nitric acid

(65%)/cellulose mixture and the criteria for Packing Group I and II are not met. *Unstable Reactives*: Substances that may decompose, condense or self-react, but only under conditions of high temperature and/or pressure and have little or no potential to cause significant heat generation or explosive hazard.

HYDROGEN SULFIDE (1 ppm-4%)/METHANE (0-5%)/CARBON DIOXIDE (1 ppm-12.5%)/OXYGEN (0-22.5%)/ NITROGEN (Balance)GAS MIXTURE MSDS

EFFECTIVE DATE: JULY 22, 2003

PAGE 18 OF 14

MATH0069

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM

HAZARD RATINGS (continued):

PHYSICAL HAZARD (continued):

1 (continued): Substances that readily undergo hazardous polymerization in the absence of inhibitors.); **2 (Water Reactivity):** Materials that may react violently with water. *Organic Peroxides:* Materials that, in themselves, are normally unstable and will readily undergo violent chemical change, but will not detonate. These materials may also react violently with water. *Explosives:* Division 1.4 – Explosive substances where the explosive effect are largely confined to the package and no projection of fragments of appreciable size or range are expected. An external fire must not cause virtually instantaneous explosion of almost the entire contents of the package. *Compressed Gases:* Pressurized and meet OSHA definition but < 514.7 psi absolute at 21.1°C (70°F) [500 psig]. *Pyrophorics:* No Rating. *Oxidizers:* Packing Group II *Solids:* any material that, either in concentration tested, exhibits a mean burning time of less than or equal to the mean burning time of a 2:3 potassium bromate/cellulose mixture and the criteria for Packing Group I are not met. *Liquids:* any material that exhibits a mean pressure rise time less than or equal to the pressure rise of a 1:1 aqueous sodium chlorate solution (40%)/cellulose mixture and the criteria for Packing Group I are not met. *Unstable Reactives:* Substances that may polymerize, decompose, condense, or self-react at ambient temperature and/or pressure, but have a low potential for significant heat generation or explosion. Substances that readily form peroxides upon exposure to air or oxygen at room temperature); **3 (Water Reactivity):** Materials that may form explosive reactions with water. *Organic Peroxides:* Materials that are capable of detonation or explosive reaction, but require a strong initiating source, or must be heated under confinement before initiation; or

materials that react explosively with water. *Explosives:* Division 1.2 – Explosive substances that have a fire hazard and either a minor blast hazard or a minor projection hazard or both, but do not have a mass explosion hazard. *Compressed Gases:* Pressure \geq 514.7 psi absolute at 21.1°C (70°F) [500 psig]. *Pyrophorics:* No Rating. *Oxidizers:* Packing Group I *Solids:* any material that, in either concentration tested, exhibits a mean burning time less than the mean burning time of a 3:2 potassium bromate/cellulose mixture. *Liquids:* Any material that spontaneously ignites when mixed with cellulose in a 1:1 ratio, or which exhibits a mean pressure rise time less than the pressure rise time of a 1:1 perchloric acid (50%)/cellulose mixture. *Unstable Reactives:* Substances that may polymerize, decompose, condense or self-react at ambient temperature and/or pressure and have a moderate potential to cause significant heat generation or explosion.); **4 (Water Reactivity):** Materials that react explosively with water without requiring heat or confinement. *Organic Peroxides:* Materials that are readily capable of detonation or explosive decomposition at normal temperature and pressures. *Explosives:* Division 1.1 & 1.2-explosive substances that have a mass explosion hazard or have a projection hazard. A mass explosion is one that affects almost the entire load instantaneously. *Compressed Gases:* No Rating. *Pyrophorics:* Add to the definition of Flammability “4”. *Oxidizers:* No “4” rating. *Unstable Reactives:* Substances that may polymerize, decompose, condense or self-react at ambient temperature and/or pressure and have a high potential to cause significant heat generation or explosion.). PPE Rating B: Hand and eye protection is required for routine chemical use. PPE Rating C: Hand, eye, and body protection may be required for routine chemical use.

DEFINITIONS OF TERMS (Continued)

NATIONAL FIRE PROTECTION ASSOCIATION HAZARD RATINGS:

HEALTH HAZARD: **0** (material that on exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials); **1** (materials that on exposure under fire conditions could cause irritation or minor residual injury); **2** (materials that on intense or continued exposure under fire conditions could cause temporary incapacitation or possible residual injury); **3** (materials that can on short exposure could cause serious temporary or residual injury); **4** (materials that under very short exposure could cause death or major residual injury).

FLAMMABILITY HAZARD: **0** Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand. **1** Materials that must be preheated before ignition can occur. Materials in this degree require considerable preheating, under all ambient temperature conditions, before ignition and combustion can occur. **2** Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur. Materials in this degree would not under normal conditions form hazardous atmospheres with air, but under high ambient temperatures or under moderate heating could release vapor in sufficient quantities to produce hazardous atmospheres with air. **3** Liquids and solids that can be ignited under almost all ambient temperature conditions. Materials in this degree produce hazardous atmospheres with air under almost all ambient temperatures or, though unaffected by ambient temperatures, are readily ignited under almost all conditions. **4** Materials that will rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and will burn readily.

INSTABILITY HAZARD: **0** Materials that in themselves are normally stable, even under fire conditions. **1** Materials that in themselves are normally stable, but that can become unstable at elevated temperatures and pressures. **2** Materials that readily undergo violent chemical change at elevated temperatures and pressures. **3** Materials that in themselves are capable of detonation or explosive decomposition or explosive reaction, but that require a strong initiating source or that must be heated under confinement before initiation. **4** Materials that in themselves are readily capable of detonation or explosive decomposition or explosive reaction at normal temperatures and pressures.

FLAMMABILITY LIMITS IN AIR: Much of the information related to fire and explosion is derived from the National Fire Protection Association (NFPA). **Flash Point** - Minimum temperature at which a liquid gives off sufficient vapors to form an ignitable mixture with air. **Autoignition Temperature:** The minimum temperature required to initiate combustion in air with no other source of ignition. **LEL** - the lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source. **UEL** - the highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source.

TOXICOLOGICAL INFORMATION:

Human and Animal Toxicology: Possible health hazards as derived from human data, animal studies, or from the results of studies with similar compounds are presented. Definitions of some terms used in this section are: **LD₅₀** - Lethal Dose (solids & liquids) which kills 50% of the exposed animals; **LC₅₀** - Lethal Concentration (gases) which kills 50% of the exposed animals; **ppm** concentration expressed in parts of material per million parts of air or water; **mg/m³** concentration expressed in weight of substance per volume of air; **mg/kg** quantity of material, by weight, administered to a test subject, based on their body weight in kg. Other measures of toxicity include **TDLo**, the lowest dose to cause a symptom and **TCLo** the lowest concentration to cause a symptom; **TD₀**, **LDLo**, and **LDo**, or **TC**, **TCo**, **LCLo**, and **LCo**, the lowest dose (or concentration) to cause lethal or toxic effects. **Cancer Information:** The sources are: **IARC** - the International Agency for Research on Cancer; **NTP** - the National Toxicology Program, **RTECS** - the Registry of Toxic Effects of Chemical Substances, **OSHA** and **CAL/OSHA**. IARC and NTP rate chemicals on a scale of decreasing potential to cause human cancer with rankings from 1 to 4. Subrankings (2A, 2B, etc.) are also used. **Other Information:** **BEI** - ACGIH Biological Exposure Indices, represent the levels of determinants which are most likely to be observed in specimens collected from a healthy worker who has been exposed to chemicals to the same extent as a worker with inhalation exposure to the TLV.

ECOLOGICAL INFORMATION:

BCF = Bioconcentration Factor, which is used to determine if a substance will concentrate in lifeforms which consume contaminated plant or animal matter; **EC** is the Effect Concentration in water; **EC₅₀** is the Effect Concentration for 50% of the organisms exposed; **NOEC** is the No Observed Effect Concentration; **MATC** is the Maximum Acceptable Toxicant Concentration; **NOLC** is the No Observed Lethal Concentration; **TL_m** = median threshold limit; Coefficient of Oil/Water Distribution is represented by **log K_{ow}** or **log K_{oc}** and is used to assess a substance's behavior in the environment.

REGULATORY INFORMATION:

U.S. and CANADA:

ACGIH: American Conference of Governmental Industrial Hygienists, a professional association which establishes exposure limits. This section explains the impact of various laws and regulations on the material. **EPA** is the U.S. Environmental Protection Agency. **NIOSH** is the National Institute of Occupational Safety and Health, which is the research arm of the U.S. Occupational Safety and Health Administration (**OSHA**). **WHMIS** is the Canadian Workplace Hazardous Materials Information System. **DOT** and **TC** are the U.S. Department of Transportation and the Transport Canada, respectively. Superfund Amendments and Reauthorization Act (**SARA**); the Canadian Domestic/Non-Domestic Substances List (**DSL/NDSL**); the U.S. Toxic Substance Control Act (**TSCA**); Marine Pollutant status according to the **DOT**; the Comprehensive Environmental Response, Compensation, and Liability Act (**CERCLA** or **Superfund**); and various state regulations. This section also includes information on the precautionary warnings which appear on the material's package label. **OSHA** - U.S. Occupational Safety and Health Administration.

HYDROGEN SULFIDE (1 ppm-4%)/METHANE (0-5%)/CARBON DIOXIDE (1 ppm-12.5%)/OXYGEN (0-22.5%)/NITROGEN (Balance)GAS MIXTURE MSDS

