



# MultiRAE

Wireless Portable Six-Gas Monitor with Advanced VOC Detection Capability



The MultiRAE is the most advanced wireless portable chemical detector on the market. The MultiRAE's cutting-edge PID sensor detects volatile organic compounds (VOCs), and supports over 30 electrochemical, NDIR, and catalytic sensors to detect up to five additional threats. These include: toxic and combustible gases, oxygen deficiency/enrichment, and carbon dioxide.

The MultiRAE's wireless capability elevates worker protection to the next level by providing safety officers real-time access to instrument readings and alarm status from any location for better visibility and faster incident response.

- The most advanced wireless portable chemical detector on the market
- Highly versatile and customizable for different applications
- Man Down Alarm with real-time remote wireless notification
- Easy maintenance with replaceable sensors, pump, and plug-and-play battery
- Fully automated bump testing and calibration with AutoRAE2<sup>1</sup>

## KEY FEATURES

Wireless. Versatile. Proven.

- Wireless access to real-time instrument readings and alarm status from any location
- Unmistakable five-way local and remote wireless notification of alarm conditions
- Over 30 interchangeable sensor options, including 0.1 to 5,000 ppm PID
- Intelligent sensors store calibration data, so they can be swapped in the field<sup>2</sup>
- Extensive on-board gas libraries (190 VOCs and 55 combustible gases)
- Largest display in its class
- Continuous datalogging (6 months for 5 sensors, 24x7)

## APPLICATIONS

- Industrial hygiene, personal protection, and multi-gas leak detection in industries such as:
  - Oil and gas
  - Chemical
  - Aviation (wing tank entry)
  - Shipping / Marine
  - Environmental
  - Pharmaceutical
- HazMat response
- Clandestine drug labs



MultiRAE used for worker exposure monitoring at an oil refinery






AutoRAE 2  
Compatible



### SPECIFICATIONS

#### Instrument Specifications<sup>5</sup>

Size	7.6" H x 3.8" W x 2.6" D (193 x 96.5 x 66 mm)
Weight	31 oz. (880 g)
Sensors	Over 30 intelligent interchangeable field-replaceable sensors including PID for VOCs, electrochemical sensors for toxic gases and oxygen, combustible LEL and NDIR sensors, and CO <sub>2</sub> NDIR sensor
Battery Options	- Rechargeable Li-ion (~12-hr. runtime, < 6-hr. recharge time) - Extended duration Li-ion (~18-hr. runtime, < 9-hr. recharge time) - Alkaline adapter with 4 x AA batteries (~6-hr. runtime)
Display	Monochrome graphical LCD display (128 x 160) with backlighting. Automatic screen "flip" feature.
Display Readout	- Real-time reading of gas concentrations; PID measurement gas and correction factor; battery status; datalogging on/off; wireless on/off and reception quality. - STEL, TWAA, peak, and minimum values
Keypad Buttons	3 operation and programming keys (Mode, Y/+, and N/-)
Sampling	Built-in pump. Average flow rate: 250 cc/min. Auto shutoff in low-flow conditions
Calibration	Automatic with AutoRAE 2 Test and Calibration System <sup>1</sup> or manual
Alarms	Wireless remote alarm notification; multi-tone audible (95 dB @ 30 cm), vibration, visible (flashing bright red LEDs), and on-screen indication of alarm conditions - Man Down Alarm with pre-alarm and real-time remote wireless notification
Datalogging	- Continuous datalogging (6 months for 5 sensors at 1-minute intervals, 24/7) - User-configurable datalogging intervals (from 1 to 3,600 seconds)
Communication and Data Download	- Data download and instrument set-up and upgrades on PC via charging and PC comm. cradle, travel charger, or AutoRAE 2 Automated Test and Calibration System <sup>1</sup> - Wireless data and alarm status transmission via built-in RF modem (optional)
Wireless Network	RAE Systems Dedicated Wireless Network
Wireless Frequency	ISM license-free bands
Wireless Range (Typical)	656 feet (200 meters)
Operating Temperature	-4° to 122°F (-20° to 50°C)
Humidity	0% to 95% relative humidity (non-condensing)
Dust and Water Resistance	IP-65 rating
Hazardous Location Approvals	CSA:  Class I, Division 1, Groups A, B, C and D, T4 ATEX:  0575  II 2G Ex ia d IIC T4 Gb IECEx: Ex ia d IIC T4 Gb
CE Compliance (European Conformity)	EMC directive: 2004/108/EC. R&TTE directive: 1999/5/EC. ATEX directive: 94/9/EC
EMI/RFI	No effect when exposed to 0.43mW/cm <sup>2</sup> RF interference from a 5-watt transmitter at 12"
Performance Tests	MIL-STD-810F compliant. LEL CSA C22.2 No. 152; ISA-12.13.01
Languages	Arabic, Chinese, Czech, Danish, Dutch, English, French, German, Indonesian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Russian, Spanish, and Swedish
Warranty	- Two years on non-consumable components and catalytic LEL, CO, H <sub>2</sub> S, and O <sub>2</sub> sensors - One year on all other sensors, pump, battery, and other consumable parts

1 Contact RAE Systems for availability.

2 RAE Systems recommends calibrating sensors on installation.

3 Additional equipment and/or software licenses may be required to enable remote wireless monitoring and alarm transmission.

4 The CO + H<sub>2</sub>S combo sensor is required for a 6-gas configuration.

5 Specifications are subject to change.

[www.raesystems.com](http://www.raesystems.com)

RAE Systems Inc.  
3775 North First Street  
San Jose, CA 95134 USA  
raesales@raesystems.com

USA/Canada 1-877-723-2878  
Europe +45 8652 5155  
Middle East +971 4 440 5949  
China +86 10 5885 8788  
Asia Pacific +852 2669 0828

DS-1070-01

#### Sensor Specifications<sup>5</sup>

PID Sensors	Range	Resolution
VOC 10.6 eV (HR)	0 to 5,000 ppm	0.1 ppm
VOC 9.8 eV <sup>1</sup>	0 to 1,000 ppm	0.1 ppm
Combustible Sensors	Range	Resolution
Catalytic LEL	0 to 100% LEL	1% LEL
NDIR (0-100% LEL Methane)	0 to 100% LEL	1% LEL
NDIR (0-100% Vol. Methane)	0 to 100% Vol.	0.1% Vol.
Carbon Dioxide Sensor	Range	Resolution
Carbon Dioxide (CO <sub>2</sub> ) NDIR	0 to 50,000 ppm	100 ppm
Electrochemical Sensors	Range	Resolution
Ammonia (NH <sub>3</sub> )	0 to 100 ppm	1 ppm
Carbon Monoxide (CO)	0 to 500 ppm	1 ppm
Carbon Monoxide (CO), Ext. Range	0 to 2,000 ppm	10 ppm
Carbon Monoxide (CO), H <sub>2</sub> -comp.	0 to 2,000 ppm	10 ppm
Carbon Monoxide (CO) + Hydrogen Sulfide (H <sub>2</sub> S) Combo	0 to 500 ppm 0 to 200 ppm	1 ppm 0.1 ppm
Chlorine (Cl <sub>2</sub> )	0 to 50 ppm	0.1 ppm
Chlorine Dioxide (ClO <sub>2</sub> )	0 to 1 ppm	0.03 ppm
Ethylene Oxide (EtO-A)	0 to 100 ppm	0.5 ppm
Ethylene Oxide (EtO-B)	0 to 10 ppm	0.1 ppm
Ethylene Oxide (EtO-C), Ext. Range	0 to 500 ppm	10 ppm
Formaldehyde (HCHO)	0 to 10 ppm	0.01 ppm
Hydrogen (H <sub>2</sub> )	0 to 1,000 ppm	2 ppm
Hydrogen Chloride (HCl)	0 to 15 ppm	1 ppm
Hydrogen Cyanide (HCN)	0 to 50 ppm	0.5 ppm
Hydrogen Fluoride (HF)	0 to 10 ppm	0.1 ppm
Hydrogen Sulfide (H <sub>2</sub> S)	0 to 100 ppm	0.1 ppm
Hydrogen Sulfide (H <sub>2</sub> S), Ext. Range	0 to 1,000 ppm	1 ppm
Methyl Mercaptan (CH <sub>3</sub> -SH)	0 to 10 ppm	0.1 ppm
Nitric Oxide (NO)	0 to 250 ppm	0.5 ppm
Nitrogen Dioxide (NO <sub>2</sub> )	0 to 20 ppm	0.1 ppm
Oxygen (O <sub>2</sub> )	0 to 30% Vol.	0.1% Vol.
Phosgene (COCl <sub>2</sub> )	0 to 1 ppm	0.02 ppm
Phosphine (PH <sub>3</sub> )	0 to 20 ppm	0.1 ppm
Phosphine (PH <sub>3</sub> ), Ext. Range	0 to 1,000 ppm	1 ppm
Sulfur Dioxide (SO <sub>2</sub> )	0 to 20 ppm	0.1 ppm

### ORDERING INFORMATION (MODELS: PGM-622X)

- Wireless<sup>1,3</sup> and non-wireless configurations are available
- Refer to the Portables Pricing Guide for part numbers for monitors and accessories

**Toll-Free: 877-723-2878**