

FIELD Environmental Instruments

Equipment Rental and Field Supplies

Schonstedt Instrument Company

"Your Needs Are Our Business"

Toll-Free
800-393-4009

**Model GA-72Cd
Magnetic Locator**



The model GA-72Cd Magnetic Locator detects the magnetic field of ferromagnetic objects. It responds to the difference in the magnetic field between two sensors, which are spaced about 14 inches apart.

The GA-72Cd is unique because it provides an audio signal and visual indication of both signal strength and polarity. Although most objects can be located using either indications, simultaneous use of both types will help you pinpoint your target and determine its orientation and identity magnetically detectable nonmetallic duct and cable.

SPECIFICATIONS

Input Power:	Supplied by two lithium 9-V batteries
Battery Life:	60 Hours (intermittent usage)
Audio:	
Output Option Switch at "A"	Signal increases or decreases in volume with gradient-field intensity
Output Option Switch at "B"	Signal increases or decreases in frequency with gradient-field intensity
Visual:	Digital readout expanding bar graphs Indicate polarity (positive or negative) and Relative strength of the magnetic field
Battery Check:	BATT 4-segment LCD
Weight:	Approximately 2.5lbs. (1.14kg)
Operating Temperature:	-13° to 140°F (-25°C to 60°C)
Overall Length:	34.5 in. (87.6cm)
Waterproof Length:	21 in. (53.3cm)
Nominal Sensor Spacing:	14 in. (35.6cm)
Construction:	Rugged, all solid state

99 Miller Avenue
Braddock, PA 15104

800-393-4009
Fax 412-271-5083

info@
fieldenvironmental.com

Visit us soon on the web
www.
fieldenvironmental.com

**Inquiries and
orders
800-393-4009**