FIELD Environmental Instruments

VelociCheck

Model 8340
Air Velocity Meter

Equipment Rental and Field Supplies

"Your Needs Are Our Business"



Toll-Free 800-393-4009

TSI's line of VELOCICHECK Air Velocity Meters provides a reliable, accurate and easy way to make air velocity measurements. The VELOCICHECKs are small, pocket-sized meters that require no training; just pick up the meter and start taking readings. These meters provide a cost-effective way to quickly take the measurements you need.

FEATURES

- □ Listed by Underwriters Laboratories as intrinsically safe for use in hazardous locations for Divisions 1 and 2 in Class I, Groups C and D; Class II, Groups E, F and G; and Class III. □ Velocity range of 0 to 10.00 m/s □ Easy-to-read digital display
- $\hfill \square$ Slow and fast time constant modes available to smooth the display when measuring fluctuating flows
- ☐ Includes a battery check that monitors battery level to ensure accurate readings
- ☐ NIST*-traceable calibration certificate

SPECIFICATIONS

Velocity

Range: 0 to 10.00 m/s (0 to 2,000 ft/min)

Accuracy: 5.0% of reading or ±0.025 m/s (±5 ft/min) whichever is greater

External Meter Dimensions (all models)

Size Measurements: 70 mm x 33 mm x 132 mm (2.75 in. x 1.3 in. x 5.2 in.)

Meter Probe Type

Description: Retractable Material: Stainless steel

Meter Probe Dimensions

Probe Length: 79 mm (3.1 in.) length when extended Probe

Diameter: 6.4 mm (0.25 in.)

Operating Temperature Range

Instrument: 0 to 50°C (32 to 122°F) Probe: 0 to 50°C (32 to 122°F)

Battery Life:

Minimum 20 hours at 0.5 m/s (100 ft/min) using alkaline batteries

Display

Type: Digital

Description: 4 1/2 digits, 10 mm (0.4 in.) high

Time Constant

Fast mode: 3-second averaging Slow mode: 12-second averaging

Power Requirements

Four AA-size batteries, alkaline only (provided)

Safety Rating

UL listed intrinsically safe for use in hazardous locations for Divisions 1 and 2 in Class I, Groups C and D; Class II, Groups E, F and G; and Class III when used with alkaline batteries

301 Brushton Avenue Suite A Pittsburgh, PA 15221

800-393-4009

Fax 412-436-2616

info@ fieldenvironmental.com

Visit us on the web $\label{eq:www.}$ field environmental.com

Inquiries and orders 800-393-4009