# FIELD Environmental Instruments

### Equipment Rental and Field Supplies

## VICTOREEN

Model 190 Radiation Monitor

"Your Needs Are Our Business"

# SPECIFICATIONS

### Toll-Free 800-393-4009

The Victoreen 190 is a portable, battery-operated general purpose survey meter for use with most scintillation and Geiger-Mueller (GM) radiation detection, proportional counting probes, and neutron probes. The design combines CMOS microprocessor technology, automatic range changing, and a Liquid Crystal Display (LCD) into an easy to use instrument.

The 190 is housed in a light-weight, plastic case designed for portability and durability. Measurement results are indicated on the front panel LCD. The display includes:

- A 51-element analog bar graph near the top of the display to provide real time response.
- " A scale multiplier, located below the bargraph, that relates the display units to the displayed bargraph value.
- Detector range bargraph consisting of five horizontal bars that indicate the quantity of the dynamic range of the detector in use
- A 16 character alphanumeric display that (1) provides a digitized average of the bargraph value or integrated reading with elapsed time, and (2) displays operational information (such as response time changes or changes in the units of display)
  - A backlight, activated by either of two front panel switches, that provides for operation in dark environments

Operating Range:	0.001 mR/hr to 1 R/hr or 1 to 1,000,000 cpm	99 Miller Avenue
		Braddock, PA15104
Accuracy:	Within 10% of reading between 10 to 100% of full scale	800-393-4009
Ranges:	6 decades are available for calibation; (detector dependent)	Fax 412-271-5083
Deadtime Correction:	Provided above 1000CPM	
Jam Detection:	Adjustable level for determing jam condition; provided in probe adapter modules	info@ fieldenvironmental.com
Alarm:	Can be set on any decade at 10% to 100% (in increments of 10%) of full scale	Visit us soon on the web www.
Warm-up Time:	15 seconds (diagnostic testing)	fieldenvironmental.com
Power Source:	Four 9-volt alkaline batteries	Inquiries and orders
Operating Time:	200 hours	800-393-4009