

WELL-VU SYSTEMS

FISHEYE CAMERA

Model #: WV-300FE, WV-C500FE, 700FE, 1000FE
(Also available in motorized)



CABLE LENGTH: 300, 500, 700, 1000, 1250 & 1500 feet
CAMERA SPECS: 1 1/2" OD, high resolution, 1 lux 1/3" CCD, 550 line resolution. 180° Fisheye lens on the camera allows you to see the sides and down at the same time.

LIGHT SOURCE: 18 LED white lights emitted at a 22° angle to eliminate problems with particle reflection

DVCC: Digital Video Command Console

VIDEO OUT: Standard NTSC format

POWER SOURCE: 12VDC

CLAMP-ON OSD: (On-Screen Display Encoder), feet or meters display

GPS DATA PORT: Allows for connection of many GPS unit to put Lat/Lon, Time and date stamp on video

SHIPPING WEIGHT: 300 (100 lbs), 500 (115 lbs), 700 (125 lbs), 1000 (135 lbs),



MOTORIZED WELL-VU SYSTEM with DVCC

A full turn key system including the new digital video control console (DVCC) and detachable camera head.

CABLE LENGTH: 1000, 1250 & 1500 feet

CAMERA SPECS: 1 1/2" OD, high resolution, 1 lux 1/3" CCD, 550 line resolution

LIGHT SOURCE: 18 LED white lights emitted at a 22° angle to eliminate problems with particle reflection

POWER SOURCE: 12VDC

DVCC: Digital Video Command Console, 7" standard

VIDEO OUT: Standard NTSC format

CLAMP-ON OSD: (On-Screen Display Encoder) feet or meters display

DATA GPS: On board GPS chip



MANUAL CRANK WELL-VU SYSTEM with DVCC

Model #: WV-C300C, WV-C500C, WV-C700C & WV-C1000C

A full turn key system including the new digital video control console (DVCC) and detachable camera head.

CABLE LENGTH: 300, 500, 700, 1000, 1250 & 1500 feet
CAMERA SPECS: 1 1/2" OD, high resolution, 1 lux 1/3" CCD, 550 line resolution

LIGHT SOURCE: 18 LED white lights emitted at a 22° angle to eliminate problems with particle reflection

DVCC: Digital Video Command Console

VIDEO OUT: Standard NTSC format

POWER SOURCE: 12VDC

CLAMP-ON OSD: (On-Screen Display Encoder), feet or meters display

GPS DATA PORT: Allows for connection of many GPS unit to put Lat/Lon, Time and date stamp on video

SDM SERIES

Manual Crank with Display Components
MODEL #: WV-C300SDM, WV-C500SDM, WV-C500SDM & WV-C1000SDM



CABLE LENGTH: 300, 500, 700, 1000, 1250 & 1500 feet
CAMERA SPECS: 1 1/2" OD, high resolution, 1 lux 1/3" CCD, 550 line resolution

LIGHT SOURCE: 15 LED white lights emitted at a 22° angle to eliminate problems with particle reflection

POWER SOURCE: 12VDC

VIDEO OUT: Standard NTSC format

BATTERY & CHARGER: 12VDC 7ah sealed lead-acid battery, 12VDC charger 7" LCD (included)

MONITOR: (On-Screen Display Encoder), feet or meters display

CLAMP-ON OSD: Allows for connection of many GPS unit to put Lat/Lon, Time and date stamp on video

GPS DATA PORT: Allows for connection of many GPS unit to put Lat/Lon, Time and date stamp on video