FIELD Environmental Instruments

YSI

556 MPS

Groundwater Monitoring Multi-Probe System

Equipment Rental and Field Supplies

"Your Needs Are Our Business"



Toll-Free 800-393-4009

Rugged, reliable and waterproof, the YSI 556 MPS (Multiprobe System) combines the versatility of an easy-to-use, easy-to-read handheld unit with all the functionality of a multiparameter system.

Featuring a waterproof IP-67, impact-resistant case, the YSI 556 MPS simultaneously measures dissolved oxygen, pH, conductivity, temperature, and ORP. The YSI 556 MPS assists the user in conforming to GLP standards.

FEATURES:

Simultaneous measurement of:

- -Dissolved Oxygen
- -pH
- -Conductivity
- -Temperature
- -ORP

Easy to use, screw-on cap DO membranes

Stores over 49,000 data sets, time and date stamped Compatible with EcoWatchTM for WindowsTM software

Field-replaceable DO electrode modules; pH and pH/ORP probes

Optional flow cell

Optional Barometer Sensor Specifications available

SPECIFICATIONS

Dissolved Oxygen Range: 0 to 55% air saturation

(% saturation) Accuracy: 0 to 200% air saturation, ± 2% air saturation,

whichever is greater; 200 to 500% air saturation, +

6% of the reading

Resolution: 0.1% air saturation

Dissolved Oxygen Range: 0 to 50 mg/L

Temperature

(mg/L) Accuracy: 0 to 20 mg/L, \pm 2% of the reading or 0.2mg/L, which

ever is greater; 20 to 50mg/L + 6% of the reading

Resolution: 0.01 mg/L

 Range:
 -5 to 45°C

 Accuracy:
 ± 0.15°C

 Resolution:
 0.1°C

Conductivity Range: 0 to 100 mS/cm

Accuracy: + 0.5% of reading + 0.001 mS/cm

Resolution: 0.001 mS/cm to 0.1 mS/cm (range-dependent)

Salinity Range: 0 to 70 ppt

Accuracy: ± 1.0% of reading or 0.1 ppt, whichever is greater

Resolution: 0.01 ppt
Range: 0 to 14 units
Accuracy: ± 0.2 units

Resolution: 0.01 units
ORP Range: -999 to +999 mV

Accuracy: $\pm 20 \text{ mV}$ Resolution: 0.1 mV

99 Miller Avenue

Braddock, PA 15104

800-393-4009

Fax 412-271-5083

info@

fieldenvironmental.com

Visit us soon on the web

www.

fieldenvironmental.com

Inquiries and orders

800-393-4009