

Material Name: HYDROGEN SDS ID: MAT11120

* * * Section 1 - IDENTIFICATION* * *

Manufacturer Information

MATHESON TRI-GAS, INC. General Information: 1-800-416-2505

150 Allen Road, Suite 302 Emergency #: 1-800-424-9300 (CHEMTREC)

Basking Ridge, NJ 07920 Outside the US: 703-527-3887 (Call collect)

Material Name: HYDROGEN

Trade Names/Synonyms

MTG MSDS 49; HYDROGEN GAS; HYDROGEN COMPRESSED; HYDROGEN (H2); DIHYDROGEN; UN 1049; H2; RTECS: MW8900000

Chemical Family

inorganic, gas

Product Use

industrial

Restrictions on Use

None known.

* * * Section 2 - HAZARDS IDENTIFICATION* * *

GHS Classification

Flammable gas, Category 1

Gas under pressure, Compressed gas

Acute Toxicity (Inhalation), Category 4

GHS LABEL ELEMENTS

Material Name: HYDROGEN SDS ID: MAT11120

Symbol(s)



Signal Word

DANGER

Hazard Statement(s)

Extremely flammable gas

Contains gas under pressure; may explode if heated

Harmful if inhaled

Precautionary Statement(s)

Prevention

Keep away from heat, sparks, open flame, and hot surfaces - No smoking. Avoid breathing gas. Use only outdoors or in a well-ventilated area.

Response

Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Storage

Store in a well-ventilated place.

Protect from sunlight.

Disposal

Dispose in accordance with all applicable regulations.

Other Hazards which do not Result in Classification

May cause frostbite upon sudden release of compressed gas. May cause asphyxia.

* * * Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS* * *

Page 2 of 11 Issue Date: 09/12/2011 Revision 1.0200 Print Date: 12/14/2011

Material Name: HYDROGEN SDS ID: MAT11120

CAS#	Component	Percent
1333-74-0	HYDROGEN	100

* * * Section 4 - FIRST AID MEASURES* * *

Inhalation

If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

Skin

If frostbite or freezing occur, immediately flush with plenty of lukewarm water (100-105 F, 38-41 C). DO NOT USE HOT WATER. If warm water is not available, gently wrap affected parts in blankets. Get immediate medical attention.

Eyes

Immediately flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

Ingestion

If a large amount is swallowed, get medical attention.

Note to Physicians

For inhalation, consider oxygen.

Symptoms: Immediate

suffocation, frostbite

Symptoms: Delayed

No information on significant adverse effects.

* * * Section 5 - FIRE FIGHTING MEASURES* * *

See Section 9 for Flammability Properties

Specific Hazards Arising from the Chemical

Severe fire hazard. Severe explosion hazard. Vapor/air mixtures are explosive. Pressurized containers may rupture or explode if exposed to sufficient heat. Electrostatic discharges may be generated by flow or agitation resulting in ignition or explosion. Burns with invisible flame.

Extinguishing Media

carbon dioxide, regular dry chemical

Page 3 of 11 Issue Date: 09/12/2011 Revision 1.0200 Print Date: 12/14/2011

Material Name: HYDROGEN SDS ID: MAT11120

Large fires: water spray or fog

Unsuitable Extinguishing Media

None known.

Protective Equipment and Precautions for Firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Fire Fighting Measures

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. For fires in cargo or storage area: Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. If this is impossible then take the following precautions: Keep unnecessary people away, isolate hazard area and deny entry. Let the fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For tank, rail car or tank truck: Stop leak if possible without personal risk. Let burn unless leak can be stopped immediately. For smaller tanks or cylinders, extinguish and isolate from other flammables. Evacuation radius: 800 meters (1/2 mile). Do not attempt to extinguish fire unless flow of material can be stopped first. Flood with fine water spray. Cool containers with water spray until well after the fire is out. Apply water from a protected location or from a safe distance. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas. Evacuate if fire gets out of control or containers are directly exposed to fire. Evacuation radius: 500 meters (1/3 mile). Consider downwind evacuation if material is leaking. Stop flow of gas.

* * * Section 6 - ACCIDENTAL RELEASE MEASURES* * *

Personal Precautions

Wear personal protective clothing and equipment, see Section 8.

Environmental Precautions

Avoid release to the environment.

Methods for Containment

Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Avoid heat, flames, sparks and other sources of ignition. Do not touch spilled material. Stop leak if possible without personal risk. Reduce vapors with water spray.

Cleanup Methods

Keep unnecessary people away, isolate hazard area and deny entry. Remove sources of ignition. Ventilate closed spaces before entering.

Material Name: HYDROGEN SDS ID: MAT11120

* * * Section 7 - HANDLING AND STORAGE* * *

Handling Procedures

Wash thoroughly after handling.

Storage Procedures

Store and handle in accordance with all current regulations and standards. Store in a well-ventilated place. Protect from sunlight. Grounding and bonding required. Subject to storage regulations: U.S. OSHA 29 CFR 1910.101. Keep separated from incompatible substances.

* * * Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION* * *

Component Exposure Limits

HYDROGEN (1333-74-0)

ACGIH: Simple asphyxiant

Component Biological Limit Values

There are no biological limit values for any of this product's components.

Engineering Controls

Ventilation equipment should be explosion-resistant if explosive concentrations of material are present. Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

Eyes/Face

For the gas: Eye protection not required, but recommended. For the liquid: Wear splash resistant safety goggles. Contact lenses should not be worn. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Protective Clothing

For the gas: Protective clothing is not required. For the liquid: Wear appropriate protective, cold insulating clothing.

Glove Recommendations

Wear insulated gloves.

Respiratory Protection

Under conditions of frequent use or heavy exposure, respiratory protection may be needed.

Respiratory protection is ranked in order from minimum to maximum.

Consider warning properties before use.

Page 5 of 11 Issue Date: 09/12/2011 Revision 1.0200 Print Date: 12/14/2011

Material Name: HYDROGEN SDS ID: MAT11120

For Unknown Concentrations or Immediately Dangerous to Life or Health -

Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive-pressure mode.

Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode.

* * * Section 9 - PHYSICAL AND CHEMICAL PROPERTIES* * *

Physical State: Gas Appearance: colorless gas

Color: colorless Physical Form: gas

Odor: odorless Odor Threshold: Not available

Taste: tasteless pH: Not available

Melting/Freezing Point: -259 °C Boiling Point: -253 °C

Flash Point: flammable Decomposition: Not available

Evaporation Rate: Not available LEL: 4.0 %

UEL: 75 % **Vapor Pressure:** 760 mmHg @ -253 °C

Vapor Density (air = 1): 0.07 Density: $0.08987 \text{ g/L} @ 0 ^{\circ}\text{C}$

Water Solubility: 1.82 % @ 20 °C Log KOW: Not available

Auto Ignition: 400 °C Viscosity: 0.008957 cP @26.8 °C

Molecular Weight: 2.0 Molecular Formula: H2

Solvent Solubility

Slightly Soluble: alcohol, ether

* * * Section 10 - STABILITY AND REACTIVITY* * *

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable at normal temperatures and pressure.

Page 6 of 11 Issue Date: 09/12/2011 Revision 1.0200 Print Date: 12/14/2011

Material Name: HYDROGEN SDS ID: MAT11120

Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Minimize contact with material. Containers may rupture or explode if exposed to heat.

Possibility of Hazardous Reactions

Will not polymerize.

Incompatible Materials

combustible materials, halocarbons, halogens, metal oxides, metal salts, metals, oxidizing materials

Decomposition Products

miscellaneous decomposition products

* * * Section 11 - TOXICOLOGICAL INFORMATION* * *

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

HYDROGEN (1333-74-0)

Inhalation LC50 Rat >15000 ppm 1 h

RTECS Acute Toxicity (selected)

The components of this material have been reviewed and RTECS publishes no data as of the date on this document.

Immediate Effects

suffocation, frostbite

Delayed Effects

No information on significant adverse effects.

Irritation/Corrosivity Data

No animal testing data available for skin or eyes.

RTECS Irritation

The components of this material have been reviewed and RTECS publishes no data as of the date on this document.

Page 7 of 11 Issue Date: 09/12/2011 Revision 1.0200 Print Date: 12/14/2011

Material Name: HYDROG	EN	SDS ID: MAT11120
Respiratory Sensitizer		
No data available.		
Dermal Sensitizer		
No data available.		
Carcinogenicity		
Component Carcinogenici	ity	
None of this produc	et's components are listed by ACGIH, IARC, NTP, OSHA or DFC	G.
RTECS Mutagenic		
The components of	this material have been reviewed, and RTECS publishes data	for one or more components.
Reproductive Effects Data	a	
No data available.		
RTECS Tumorigenic		
The components of	this material have been reviewed, and RTECS publishes data to	for one or more components.
Specific Target Organ Tox	kicity - Single Exposure	
No data available.		
Specific Target Organ Tox	cicity - Repeated Exposure	
No data available.		
Aspiration Hazard		
Not applicable.		
Medical Conditions Aggra	evated by Exposure	
None known.		
	* * * Section 12 - ECOLOGICAL INFORMATION*	* *
Component Analysis - Aqu	uatic Toxicity	
No LOLI ecotoxicity	data are available for this product's components.	
Persistence and Degradab	bility	
No data available.		
 Page 8 of 11	Issue Date: 09/12/2011 Revision 1.0200	 Print Date: 12/14/2011

Material Name: HYDROGEN SDS ID: MAT11120

Bioaccumulative Potential

No data available.

Mobility in Environmental Media

No data available.

* * * Section 13 - DISPOSAL CONSIDERATIONS* * *

Disposal Methods

Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001.

Component Waste Numbers

The U.S. EPA has not published waste numbers for this product's components.

* * * Section 14 - TRANSPORT INFORMATION* * *

US DOT Information

Shipping Name: Hydrogen, compressed

UN/NA #: UN1049 Hazard Class: 2.1

Required Label(s): 2.1

IMDG Information

Shipping Name: Hydrogen, compressed

UN #: UN1049 Hazard Class: 2.1

Required Label(s): 2.1

* * * Section 15 - REGULATORY INFORMATION* * *

Component Analysis

U.S. Federal Regulations

None of this products components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

Material Name: HYDROGEN SDS ID: MAT11120

SARA 311/312 Hazardous Categories

Acute Health: Yes Chronic Health: No Fire: Yes Pressure: Yes Reactive: No

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
HYDROGEN	1333-74-0	Yes	Yes	Yes	Yes	Yes

Not regulated under California Proposition 65

Component Analysis - Inventory

Listed on inventory.

Component Analysis - Inventory

Component	CAS	US	CA	EU	AU	PH	JP	KR	CN	NZ
HYDROGEN	1333-74-0	Yes	DSL	EIN	Yes	Yes	No	Yes	Yes	Yes

* * * Section 16 - OTHER INFORMATION* * *

NFPA Ratings: Health: 3 Fire: 4 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Page 10 of 11 Issue Date: 09/12/2011 Revision 1.0200 Print Date: 12/14/2011

Material Name: HYDROGEN SDS ID: MAT11120

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU -Australia: BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CN - China; CPR -Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F -Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA -National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; RID -European Rail Transport; RTECS - Registry of Toxic Effects of Chemical Substances®; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US -**United States**

Other Information

Matheson Tri-Gas, Inc. makes no express or implied warranties, guarantees or representations regarding the product or the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Matheson Tri-Gas, Inc. shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use or reliance upon the information herein.

End of Sheet MAT11120