



SPECIFICATIONS

Product Description: **VENTILATION BLOWER**
 Part Number: **9513**
 Style: **AXIAL FAN 8"**

GENERAL DESCRIPTION:

High output from a compact axial blower, designed for easy use and storage without sacrificing airflow.

CONSTRUCTION:

- Complete unit epoxy powder coated in "Safety orange".
- Flange on intake side (for optional Inlet adapter)
- Cold rolled 16-gauge steel housing
- Welded motor mount construction.
- Bottom panel enclosed to protect electrical components.
- Steel/chrome plated grill
- Carry handle made of 3-ply rubber belting.
- Equipped with four (4) rubber feet.



MOTOR:

HP: 1/3 HP CSA Approved (C22.2 No. 113)
 Voltage: 115 VAC, Single Ø, 60 Hz
 Max RPM: 3200 (Loaded at 120 Volts, 60 Hz)
 Current Draw: 3.6 A (Loaded at 120 Volts, 60 Hz)
 Capacitor: 7.5 MFD 370V AC
 Cord: 20' AWG 16/3 SJOOW 90C 300V Neoprene Medium Duty
 Switch: Inline ON/OFF, Integrated on cord.
 Plug: NEMA 5-15P 125V

FAN:

- Glass Reinforced Polypropylene (PPG) six blade fan with aluminum hub.
- Moving Fan mounted 1 5/8" from grill for safety.
- Grill Gap – 5/16".

DIMENSIONS:

Length	Width	Height	Weight
13"	13 5/8"	15"	18 Lbs

FLOW RATES: (flow rates meas. with 15' of 8" ducting)

Free Air	One 90° Bend	Two 90° Bends
1275 CFM	661 CFM	582 CFM