

- Rentals
- Supplies
- Sales
- Service

## **BESST PANACEA P200**





The Panacea P200 is the most popular in BESST's Panacea family. With a 1.75" outer diameter, the P200 is suitable for use in 2" and larger wells. It is available in Delrin plastic and in 316 stainless steel models depending on your application and budget.

The P200 also features a 60 micron alumina based ceramic filter as well as a redundant screen for thorough filtering, ensuring that no sediment becomes lodged in the valves. This advanced filter system keeps the pump operational for long-term use with little to no maintenance.

	Delrin P200 (PU-P-200-1000)	High Pressure (PU-P-200-2000)
Body Material	Delrin Plastic	316 Stainless Steel
Length (in.)	23.5	23.5
Outer Diameter (in.)	1.75	1.75
Weight (lbs.)	2	9
Maximum Pressure (PSI)	200	1500
Maximum Depth (ft. bgs.)	400	3000
Minimum Submergence (ft.)	6 ft. with Volume Booster	6 ft. with Volume Booster
Internal Volume (mL)	200	200
Standard Filter Pore Size (µm)	60, others available	60, others available
Standard Tubing OD (in.)	1/4, others available	1/4, others available
Seal Material	Buna-N, others available	Buna-N, others available
Gas Compatibility	Nitrogen, compressed air	Nitrogen, compressed air
ZIST Compatibility	2" and 4", requires adapter	2" and 4", requires adapter



