

FIELD Environmental Instruments

Equipment Rental and Field Supplies

CST

LaserMark LMH-C

"Your Needs Are Our Business"



Toll-Free
800-393-4009

With electronic sensors and motors, the unit levels itself. Features include LED power, waterproof/dust proof construction, low battery and anti-drift system indicators, 5/8" x 11 mounting thread for flat head tripods, a hard shell carrying case, batteries and an operator's manual. Leveling Accuracy: ± 15 arc seconds.

Recommended Range: up to 2,000' (610m) diameter with detector.

Laser Diode: 650nm visible red beam.

Self-Leveling Range: $\pm 3^\circ$.

Self-Leveling Speed: 1 $\frac{1}{4}$ sec. (approx.).

Power: four D cell batteries.

Battery Life: ± 75 hours intermittent use (± 25 hours using NiCad battery pack)

Operating Temperature: 22°F – 120°F (-6°C – +49°C).

Dimensions: 8"H x 6.25"W x 6.375"D.

Manufacturer's Warranty: One year.

**ORDERING
INFORMATION**

Field Environmental Instruments
99 Miller Avenue
Braddock, PA 15104

For Orders or Inquiries:
800-393-4009
Fax 412-271-5083

Visit us soon on the web
www.fieldenvironmental.com