

pH 600 and pH 610 Meters

Expanded range, resolution, and accuracy—plus increased memory and advanced communications!

New



Right: pH 610 meter

Left top: Easily download data readings into your computer.

Left bottom: Complete kits available; includes meter, carrying case and solutions.

Durable waterproof and dustproof design with IP67 rating

▼ Even with no probes attached and the battery compartment open

Push-button pH calibration at up to six points

▼ Up to 15 buffer options with auto-buffer recognition of USA, NIST, DIN, and PWB standards

Large backlit graphic display

▼ Multi-line display with electrode status indicator, calibration data, and more

User-settable "calibration due" alarm

▼ Out-of-date or unperformed calibrations are now things of the past!

Built-in real-time clock

▼ Time-and-date stamping meets Good Laboratory Practice (GLP) standards

Store up to 500 data sets

▼ Infrared IrDA wireless technology makes PC downloading convenient and easy

Set point alarms

▼ Audible warning when readings are outside set points limit

Research-grade accuracy

▼ Resolution to 0.001 pH and accuracy to ±0.002 pH on pH 610 model

Electrode status indicator

▼ Calibration data provides electrode diagnostic tool

Password protection

▼ Security for calibration and setup menus



Specifications

CE 3 year warranty

Mode		pH 600 meter	pH 610 meter
Range	pH	-2.00 to 19.99	-2.000 to 19.999
	mV	±2000 mV	±2000 mV
	Temperature	-10.0 to 110.0°C (14.0 to 230.0°F), selectable	-10.0 to 110.0°C (14.0 to 230.0°F), selectable
Resolution	pH	0.1/0.01 pH	0.1/0.01/0.001 pH
	mV	0.1 mV	0.1 mV
	Temperature	0.1°C (0.1°F)	0.1°C (0.1°F)
Accuracy	pH	±0.01 pH	±0.002 pH
	mV	±0.2 mV	±0.2 mV
	Temperature	±0.5°C (±0.9°F)	±0.5°C (±0.9°F)
Calibration	pH	Up to 6 buffer values (select from 4 sets): USA 1.68, 4.01, 7.01, 10.01, 12.45; NIST: 1.68, 4.01, 6.86, 9.18, 12.45; DIN: 1.09, 2.06, 4.65, 6.79, 9.23, 12.75, or custom buffers	
	mV	Offset up to ±150 mV	
	Temperature	Offset 0.1°C (0.1°F) increments	

Memory: up to 500 sets with GLP date and time

Output: infrared, IrDA

Real-time clock: time-and-date stamp on calibration and stored data

Temperature compensation: automatic or manual (selectable) from 0 to 100°C

Ambient operating temperature: 0 to 50°C (32 to 122°F)

Power: four 1.5 V AA batteries (included) or optional universal AC adapter, up to 500 hours continuous use

Dimensions
Meter: 7.25"L x 3.25"W x 2.25"H

Boxed: 9.2"L x 9.2"W x 2.75"H (23 x 23 x 7 cm)

Weight
Meter: 1.0 lb (0.45 kg); Boxed: 2.0 lb (0.9 kg)

Ordering Information

Catalog number	Description	Included
WD-35418-02	pH 600 meter only	Meter and batteries
WD-35418-12	pH 610 meter only	Meter and batteries
WD-35418-00	pH 600 meter	Meter, "All-in-One" probe 35816-71, and batteries
WD-35418-10	pH 610 meter	Meter, "All-in-One" probe 35816-71, and batteries
WD-35418-70	pH 600 meter kit	Meter, "All-in-One" probe, pH buffers (60 mL each of 4.01, 7.00, electrode storage solution, and rinse water), rubber boot, two electrode holders, batteries, and hard carrying case
WD-35418-80	pH 610 meter kit	Meter, "All-in-One" probe, pH buffers (60 mL each of 4.01, 7.00, electrode storage solution, and rinse water), rubber boot, two electrode holders, batteries, and hard carrying case

WD-35816-71 Replacement "All-in-One" pH/temperature probe, single-junction, epoxy body

WD-35816-72 "All-in-One" pH/temperature probe, double-junction, epoxy body

WD-35418-05 ATC probe. Use for temperature compensation with any pH electrode without built-in ATC

WD-35418-83 Optional adapter, 110/220 VAC

Multiparameter models available.
See pages 56–59.