

FIELD

Environmental Instruments

Equipment Rental and Field Supplies

Proactive

Tempest

Three-Stage Sampling Pump

"Your Needs Are Our Business"

Toll-Free
800-393-4009



The Tempest pump is capable of pumping up to 60 feet from ground level by simply connecting it to a 12 volt battery. Its reliable design is suitable for continuous sampling or purging of groundwater wells.

Features

- Passes sand, small rocks and debris without clogging or damaging the pump motors!
- Runs continuously without the need for a cool down! Unlike, the competition.
- Runs dry for up to two hours without motor damage!
- Contains a 400 hour motor life.
- Uses a sleek outside shell that minimizes well hang-ups.
- Comes ready for field use - with 70' of heavy-duty wire and alligator battery connectors.

Specifications

Tempest Pump Chart

PUMPING DEPTH IN FEET GALLONS PER MINUTE

<input type="checkbox"/> 3	3.2
<input type="checkbox"/> 10	2.8
<input type="checkbox"/> 20	2.2
<input type="checkbox"/> 30	1.75
<input type="checkbox"/> 40	1.2
<input type="checkbox"/> 50	.75
<input type="checkbox"/> 60	.40

POWER CONSUMPTION:	165 WATTS (MAX)
VOLTAGE RECOMMENDATION:	12 - 15 At Source
MAXIMUM AMP OUTPUT:	11 AMPS
MEASUREMENTS:	LENGTH 17" DIAMETER: 1.82"
CONSTRUCTED:	ABS PLASTIC & STAINLESS STEEL
DISCHARGE OUTLET:	3/8" ID x 1/2" OD
SUPPLIED WITH:	70' OF HEAVY DUTY 12 GAUGE WIRE & BATTERY CLAMPS

301 Brushton Avenue
Suite A
Pittsburgh, PA 15221

800-393-4009

Fax 412-436-2616

info@
fieldenvironmental.com

Visit us on the web
www.
fieldenvironmental.com

**Inquiries and
orders
800-393-4009**