



Soaring To New HEIGHTS


The Legacy Continues




Refineries




Fire & Hazmat



Landfills



Natural Gas



EAGLE 2

EAGLE 2



Inlet fitting

Loud buzzer (95dB)

Low flow shutoff and alarm

Internal / external hydrophobic filters

Self healing polyurethane protective overlay

Powerful internal sample pump with 125' range

4 button operation with glow in the dark text

Glove friendly handle and buttons

PID sensor for low ppm VOC detection

PPM, % LEL, or % Vol. auto-ranging combustible detection

Methane elimination for environmental use

IrDA communication port

Alarm LED's with wide visibility

3 Display modes:

- Display all gases
- Single gas view large type-auto scroll
- Single gas view large type-manual scroll

Programmable gas channel positions

3 Operating modes:


- Normal operating
- Leak check
- Bar hole sampling

Chemical, water, and dust resistant, RFI / EMI protected high impact case

Smart plug & play sensors for toxic gases

Combine catalytic and IR sensors for combustible detection

Multi lingual (5 languages)



Interchangeable Alkaline / NiMH removable battery compartment

Battery compartment thumbscrew

Specifications

Enclosure	Weatherproof, chemical resistant, anti RFI / EMI coated high impact polycarbonate - PBT blend. Can operate in rain or be set into 2.0" of water without leakage. Ergonomically balanced with rugged top mounted handle.
Dimensions	9.5" L x 5.25" W x 5.875" H (241mm L x 140mm W x 149mm H)
Weight	3.8 Lbs (1.72kg) (standard 4 gas with batteries)
Detection Principle	Catalytic combustion, electrochemical, galvanic, infrared, photo ionization, and thermal conductivity.
Sensor Life	2 Years under normal conditions.
Sampling Method	Powerful, long-life pump (over 6,000 hours) can draw samples over 125 feet. Flow rate approximately 2.0 SCFH
Display	Backlit 128 x 64 graphics display. Viewed through window in case top. Displays readings & status of all 6 channels simultaneously. Backlight, illuminates for alarms and on demand with adjustable time. Optional mode allows automatic or manual scrolling display of just one gas at a time with very large characters.
Language	Readout can display in 5 languages (English, French, German, Italian, or Spanish).
Alarms	2 Alarms per channel plus TWA and STEL alarms for toxics. The two alarms are fully adjustable for levels, latching or self reset, and silenceable.
Alarm Method	Buzzer 95 dB at 30 cm, four high intensity LED's.
Controls	4 External glove friendly push buttons for operation, demand zero, and autocalibration. Buttons also access LEL/ppm, % Vol. alarm silence, peak hold, TWA/STEL values, battery status, conversion factors, and many other features.
Continuous Operation	At 70°F, (21°C) 16 hours using alkaline batteries, or 18 hours using Ni-MH.
Power Source	4 Alkaline or Ni-MH, size C batteries (Charger has alkaline recognition to prevent battery damage if charging is attempted with alkalines).
Operating Temp. & Humidity	-4°F to 122°F (-20°C to 50°C) 0 to 95% RH, non-condensing.
Response Time	30 Seconds to 90% of range (for most gases) using standard 5 ft hose.
Safety Rating	Intrinsically Safe, Class I, Division 1, Groups A, B, C, D.
	Approvals:  
Standard Accessories	Shoulder strap, alkaline batteries, hydrophobic probe, 5 foot hose, and internal hydrophobic filter
Optional Accessories	<ul style="list-style-type: none"> • Dilution fitting (50/50) • Ni-MH batteries • Battery charger, 115 VAC, 220 VAC, or 12 VDC (charge time 4 hours) with continuous operation function • Extension hoses
Warranty	Two year material and workmanship, one year for PID sensor

Specifications subject to change without notice

Sensor Technologies

Standard 4 Gas

Specialty Sensors

Smart Toxic Sensors

Catalytic



Gas	Range	Accuracy
Hydrocarbons (CH ₄ , standard)	0 - 100% LEL	± 5% of reading or ± 2% of full scale (*)
	0 - 5% Vol. (CH ₄)	
	0 - 50,000 ppm (CH ₄)	± 50 ppm or ± 10% of reading (*)

Combustible level detection displayed in % LEL, PPM, or % volume. Methane is the standard configuration. Other combustible gases available.

Galvanic



Gas	Range	Accuracy
Oxygen (O ₂)	0 - 40% Vol. 0 - 100% Vol.	± 0.5% O ₂

A specific electrochemical sensor for oxygen monitoring.

Standard Electrochemical



Gas	Range	Accuracy
Carbon Monoxide (CO)	0 - 500 ppm	± 5% of reading ± 2 ppm (*)
Hydrogen Sulfide (H ₂ S)	0 - 100 ppm	

Extra long-life CO and H₂S sensors.

Photo ionization Detection (PID)



Gas	Range
Volatile Organic Compound (VOC)	0 - 50 ppm 0 - 2,000 ppm

Monitor low ppm VOC gases.

Infrared



Gas	Range	Accuracy
Carbon Dioxide (CO ₂)	0 - 10,000 ppm 0 - 5% Vol. 0 - 60% Vol.	± 5% of reading or ± 2% of full scale (*)
Methane (CH ₄)	0 - 100% LEL 0 - 100% Vol.	
Hydrocarbons	0 - 100% LEL 0 - 30% Vol.	

Monitor combustible gases in inert environments. Monitor wide range of CO₂.

Thermal Conductivity



Gas	Range	Accuracy
Methane (CH ₄)	0 - 100% Vol.	± 5% of reading or ± 2% of full scale (*)
Hydrogen (H ₂)	0 - 10% Vol. 0 - 100% Vol.	

Monitor % volume methane or hydrogen.

Smart Electrochemical



Gas	Range	Accuracy
Ammonia (NH ₃)	0 - 75 ppm	± 10% of reading or ± 5% of full scale (*)
Arsine (AsH ₃)	0 - 1.5 ppm	
Chlorine (Cl ₂)	0 - 3 ppm	
Hydrogen Cyanide (HCN)	0 - 15 ppm	
Phosphine (PH ₃)	0 - 1 ppm	
Sulfur Dioxide (SO ₂)	0 - 6 ppm	

Monitor a wide variety of toxic gases. Smart plug and play sensors are auto recognized and can be remotely calibrated.

Note: (*) = Whichever is greater



CONFINED SPACE ENTRY

- Monitor LEL, O₂, CO, and H₂S
- Internal sample pump
 - ◊ Pull samples up to 125'
 - ◊ Maintain steady sample flow to sensors
- Audible and visual alarms
 - ◊ 2 Ways to communicate with workers
- Ideal for refinery applications

LEAK INVESTIGATION

- Provides ppm detection of combustible gas
- Barhole mode for tracking leak migration
- Leak check with changing blink / pulsing rate
 - ◊ LED's and alarm tones increase in frequency as gas concentration increases
- Audible alarm silence
 - ◊ Perform leak investigations without alarming residents



LINE PURGE TESTING

- Thermal conductivity sensor
 - ◊ 0 to 100% volume Methane / Hydrogen range
- Autoranging IR
 - ◊ Automatically changes from % LEL to % Vol.
 - ◊ Displays appropriate unit of measure

VOC MONITORING

- Robust photo ionization detector (PID)
- Two ranges available,
 - ◊ 0-50 ppm or 0-2,000 ppm
- Can be combined with other sensors to maximize capability
- Method 21 compliant



TRANSFORMER TESTING

- Determine transformer health by sampling head space
- Measure Hydrogen (and other flammable gases) and Oxygen in nitrogen blanket
- Increasing flammable gas levels in head space indicates failing transformer

LANDFILL MONITORING

- LEL / PPM and 0-100% volume Methane
- 0-60% Carbon Dioxide range
- Can be combined with other sensors (O₂/H₂S/CO) to maximize capability



Accessories

- A. Calibration station
- B. Battery charger / continuous operation function
- C. Variety of sample hose lengths
- D. Float probe, auto shut off when probe contacts water
- E. PID service kits
- F. Calibration kits
- G. Carrying cases
- H Rechargeable Ni-MH batteries



User Selectable Options

- | | |
|-----------------------------|------------------------------|
| Date and Time | Data Log Overwrite |
| Date Format | Data Log Memory |
| Battery Type | LCD Contrast |
| Configuring Channels | Calibration Reminder |
| Combustible Gas Selection | Calibration Past Due Action |
| Catalytic Detection Units | Calibration Interval |
| Relative Response On or Off | Leak Check / Bar Hole Mode |
| Alarm Points | Bar Hole Measurement Time |
| Alarm Latching | Operation Confirmation Alert |
| Alarm Silence | Password Function On or Off |
| User and Station ID | Factory Default |
| Autocal Values | Lunch Break |
| Backlight Delay | Language |
| Auto Fresh Air | Span Factor |
| Data Log Interval | |



Made in USA



Toll Free: (800) 754-5165 • Phone: (510) 441-5656 • Fax: (510) 441-5650
www.rkieagle2.com

World Leader In Gas Detection & Sensor Technology

Authorized Distributor: