



6 Gas, Sample Draw With PID & Super Toxics

Gas Detection For Life

GX-6000



Features

- Monitor up to 6 gases
- 2 smart slots that auto recognize PID, IR, and super toxic sensors
- Library of over 600 VOCs
- PPM Leak Check mode
- Man-down alarm
- Panic alarm
- Auto display rotation
- LED Light source
- Internal sample pump
- Glove friendly buttons
- Light weight, small, rugged IP-67 design
- Interchangeable battery packs Li-ion / alkaline
- Operates up to 14 hours on Li-ion battery pack, fully recharges in 3 hours
- Field replaceable sensors, batteries, filters & pump
- Current time display

Applications

- Confined Space Entry
- Hazmat Response Teams
- Arson Investigation
- Remediation Sites
- Perimeter Monitoring
- Leak detection
- Landfill monitoring

Simply put, the GX-6000 is a game changer. This powerful hand-held instrument is capable of simultaneously monitoring up to 6 gases. In addition to the standard 4 confined space gases which include combustibles, O₂, CO, & H₂S, the GX-6000 has 2 additional smart channels that accept PID, IR or super toxic sensors. Equipped with a strong internal sample pump, a man-down alarm, a panic alarm, an LED flashlight, and large auto rotating LCD display, the GX-6000 can operate as a single gas PID unit or a multifunctional tool utilizing all 6 channels. The GX-6000 with a PID sensor will come equipped with a library of over 600 VOC gases to choose from as standard. Choosing from the library is easy with a personalized favorites list of 30 commonly used VOC's as well as a list of 8 of the most recently used VOC's.

The GX-6000 has a rugged design built for the nastiest environments. It is equipped with a removable impact-resistant rubber boot and a dust and water resistant enclosure with an IP-67 rating. With 5 bright LED lights on 3 sides of the instrument, alarms are easily seen from a variety of perspectives. With vibration and loud audible alarm, GX-6000 will easily alert users when needed.

SDM-6000 Calibration Station



RKI Instruments, Inc. • 33248 Central Ave. Union City, CA 94587 • Phone (800) 754-5165 • (510) 441-5656 • Fax (510) 441-5650

World Leader In Gas Detection & Sensor Technology
www.rkiinstruments.com

Gases & Detectable Ranges				
Gas	Measuring Range	Minimum Display	Alarm Set Points	Accuracy * Which ever is greater
Catalytic				
Hydrocarbons (CH ₄ , std)	0 - 100% LEL	1% LEL	A1: 10%LEL A2: 50%LEL	± 5% of reading or ± 2% LEL *
Galvanic				
Oxygen (O ₂)	0 - 40% Vol.	0.1% Vol.	A1: 19.5 Vol. A2: 23.5 Vol.	± 0.5% O ₂
Electro Chemical				
Carbon Monoxide (CO)	0 - 500 ppm	1 ppm	A1: 25 ppm A2: 50 ppm TWA 25 ppm STEL 200 ppm	± 5% of reading or ± 5 ppm
Hydrogen Sulfide (H ₂ S)	0 - 100 ppm	0.5 ppm	A1: 5.0 ppm A2: 30.0 ppm TWA 1.0 ppm STEL 5.0 ppm	± 5% of reading or ± 2 ppm
Toxics (EC Sensors)				
Ammonia (NH ₃)*	0 - 75 ppm 0 - 400 ppm	0.5 ppm 5 ppm	A1: 25 ppm A2: 50 ppm	± 10% of reading or ± 5% of full scale *
Chlorine (Cl ₂)*	0 - 3 ppm 0 - 10 ppm	0.05 ppm 0.1 ppm	A1: 0.5 ppm A2: 1.0 ppm	
Hydrogen Cyanide (HCN)	0 - 15 ppm	0.1 ppm	A1: 5 ppm A2: 10 ppm	
Nitrogen Dioxide (NO ₂)	0 - 9 ppm	0.05 ppm	A1: 3 ppm A2: 6 ppm	
Sulfur Dioxide (SO ₂)	0 - 6 ppm		A1: 2 ppm A2: 5 ppm	
* Available February 2016				
IR Sensors				
Carbon Dioxide (CO ₂)	0 - 10,000 ppm* 0 - 5% Vol.**	25 ppm 0.2%	A1: 5,000 ppm TWA 5,000 ppm STEL 10,000	± 5% of reading or ± 2% of full scale *
Methane (CH ₄)*	0 - 100% LEL/ 0 - 100% Vol.	Vol. 1% LEL/ 0.5% Vol	A1: 10% LEL	
Hydrocarbons**	0 - 100% LEL/ 0 - 30% Vol.		A2: 50% LEL	
** Available January 2016 * Available April 2016				
PID Sensors				
VOC	0 - 50,000 ppb	1 ppb: (< 5000 ppb) 10 ppb: (> 5,000 ppb)	A1: 5,000 ppb A2: 10,000 ppb	± 5% of full scale
	0 - 6,000 ppm	0.1 ppm: (< 600 ppm) 1 ppm: (> 600 ppm)	A1: 400 ppm A2: 1,000 ppm	

Common Specifications			
Alarm Types	Gas alarm	Man-down	Trouble
		Low and high adjustable	1st - self reset 2nd - latching
Sample Method	Sample draw pump, flow rate 0.45 LPM, 50 foot sample range		
Display	Digital LCD, autobacklight, peak bar display, auto display rotation, and customize order of gases		
Audible Alarm	95 dB at 1 ft.		
Languages	English, German, Japanese, Korean, Russian		
Continuous Operation *	14 hours on Lithium-ion battery pack. Complete recharge in 3 hours. 8 hours Alkaline battery pack (3 AA size within each pack)		
Operating Temp. & Humidity	-4°F to 122°F (-20°C ~ +50°C), 0- 95% RH non condensing		
Dimensions	2.6" W x 7.8" H x 2" D (H200 x W68 x D52 mm) 14 ounce (400g) (with lithium battery pack)		
Case Material	Dust and water resistant with IP-67 approval (exclude sample hose and probe)		
Safety Design / Approvals	Explosion proof: IECEx , ATEX , TIIS , (CSA) pending Explosion class :Ex ia IIC T4 Ga Others: CE Marking		
Standard Features	2 Smart sensors slots auto recognize sensor changes Library of over 600 VOC's User defined VOC list. Up to 30 frequently used Recent VOC list for last 8 selected gases Pump and circuit status indicators User & station ID selection menu Datalogging (interval, alarm trend, station and user ID) Snap logging - on demand data logging Demand zero / Auto zero BUMP and CAL expiration alarm Flashlight IrDA communication LEL sensor protection mode		
Standard Accessories	<ul style="list-style-type: none"> • Rubber boot • Hand strap • Probe with hydrophobic & dust filter 3' teflon lined hose • Belt clip • Tapper nozzle 		
Optional Accessories	<ul style="list-style-type: none"> • Lithium-ion battery pack & charger / alkaline battery charger • Filter set • IrDA cable 		
Warranty	Two years material (including sensors) and workmanship. One year for PID sensor		



10000363



ISO 9001

Toll Free: (800) 754-5165 • Phone: (510) 441-5656
Fax: (510) 441-5650 • www.rkiinstruments.com

Authorized Distributor: